

A Donaldson Company

A WORLD LEADER IN FUME EXTRACTION TECHNOLOGY



# **AD** Access



A compact and competitively priced fume extraction system for light duty laser marking, coding and engraving applications.

The introduction of low cost laser systems has led to the development of an entry level fume extraction solution in order to maintain safe operator working conditions and product quality.

The AD Access combines economic ownership with performance to match the small laser user. A three stage filter condition indicator is included as a standard feature, together with three stage filtration: DeepPleat pre-filter, HEPA and chemical section.





**DeepPleat pre**filter





Technology

Advanced carbon

filter (ACF)

technology

**ProTECT service** plan



**SureCHECK** quality standard

#### Key features of the AD Access

Filter condition indicator Standard

Advanced carbon filter technology (ACF) Standard

Low noise levels Standard

VOC gas sensor (Volatile Organic Compound) Optional

Filter change / System fail signal Optional

DeepPleat pre-filter Standard

Long life, low cost replacement filters Standard

Small footprint Standard


Remote stop / start interface Optional



### **Technical specification**

- 1. Unit / filter condition display
- ay 2. On / off switch
- 3. Filter compartment latch
- **4.** Hose inlet connection 50mm

- 5. Signal / interface cable
- 6. Power cable inlet
- 7. Motor cooling inlet
- 50mm <mark>8.</mark> Exhaust outlet



## Airflow through filters



Chemical filter HEPA filter



Pre filter




Clean air



Particulate

Contaminated air



Technical data				
	EU	US		
Dimensions (HxWxD)	505 x 335 x 315mm	19.88 x 13.19 x 12.40"		
Cabinet construction	Brushed stainless steel / Powder coated mild steel	Brushed stainless steel / Powder coated mild steel		
Airflow / Pressure	180m³/hr / 30mbar	106cfm / 30mbar		
Electrical data	230v 1ph 50/60Hz Full load current: 0.9 amps / 135 watts	115v 50/60Hz Full load current: 1.2 amps / 135 watts		
Noise level	< 61dBA (at typical operating speed)	< 56dBA (at typical operating speed)		
Weight	24kg	52.8lbs		
Approvals	CE	cUL, UL*		

DeepPleat pre-filter specifications			
Surface media area	1.74m² approx (18.7 ft²)		
Filter media	Borosilicate		
Filter media construction	50mm maxi fold construction with glue bead spacers (0.16ft)		
Filter efficiency	95% @ 0.9 microns		

Combined filter specifications			
HEPA filter media	Borosilicate		
HEPA media construction	Pleated with glue bead spacers		
Filter housing	Zintec mild steel		
Treated activated carbon	7kgs approx (15.4 lbs)		
Filter efficiency	99.997% @ 0.3 microns		

Part numbers						
Model	Voltage	Part no.	24V Stop / Start	Filter change / System failure signal	VOC monitoring	Hose kit
AD Access Powder coated	230V	L1842A	A2001	A2002	A2003	A1020007
AD Access Powder coated	115V	L1841A	A2001	A2002	A2003	A1020007

Replacement filters				
Model	DeepPleat pre-filter	Combined HEPA / Gas filter		
AD Access	A1030153	A1030154		

\* Certain product configurations may affect the UL certification. Please speak to your sales representative.

#### Other languages

AD Access German AD Access French

Datasheet correct at time of publishing.

Where applicable, the carbon used in BOFA units is capable of removing a wide range of VOC's, however it is the responsibility of the user to ensure the carbon is suitable for their application. For specific applications, please contact us for details.

Think before you print! Please consider the environment before printing this document.



V Tech SMT Ltd Vision House, Bandeath Industrial Estate, Throsk, Stirling, FK7 7NP T: 0044 (0) 1786 813999 F: 0044 (0) 1786 813998 E: sales@vtech-smt.co.uk W: www.vtech-smt.co.uk