

Panasonic

POWER TOOLS FOR PROFESSIONALS




PRODUCT RANGE

VALID FROM 01.07.2016

BRUSHLESS MOTOR

HIGH POWER AND EFFICIENCY



EY 74A2




EY 79A2

NEW 'SPEED CONTROL FUNCTION'

This new function allows the user to select from three different low rotation speed settings (H / M / L), based on allowable maximum speeds for metal hole saws. It greatly reduces 'run out' when using metal hole saws and prevents surface scorching on stainless steel and other materials.

| Rotation speed | Low mode | Application example (metal hole saw in mm) | High mode |
|----------------|----------|---|-----------|
| H | 300rpm | Normal steel: Ø 15-25 Stainless steel: Ø 10-15 | 1.000rpm |
| M | 200rpm | Normal steel: Ø 25- Stainless steel: Ø 15-25 | 670rpm |
| L | 150rpm | Normal steel: Ø 30- Stainless steel: Ø 20- | 500rpm |



NEW 'SELF DRILLING SCREW MODE'

New function 'Self Drilling Screw mode' starts at highest speed to cut hole and then transfers to 'H mode' (High impact) to powerfully cut initial thread. After that, load is reduced so it automatically switches to slower 'S mode' (Soft impact) to limit potential of stripping threads on fastener or material. [Less than $\varnothing 4 \times 15 \text{mm}$.]

EY 75A7



Multiple modes for all applications



3 YEAR WARRANTY – EASY TO REGISTER!

Panasonic professional power tools, Li-ion batteries and chargers meet the highest quality demands and we're now pleased to offer an extended warranty too. With cover of **3 years on the Li-ion tool** and **2 years on Li-ion battery and charger**, this service is available at no cost by simply registering your tools online within 30 days of purchase date. Scan the QR code or visit www.panasonic-powertools.eu/pt/registration.htm to register your product for a Panasonic 3 Year Warranty. Terms and conditions apply.



 www.panasonic-powertools.eu/pt/registration.htm

DRILL & DRIVER

| VOLTAGE (V) / CAPACITY (AH) | | MODEL / FEATURES | | | | | | | | | | | | | | | | | | |
|--|----------------------|--|---|--|---------|--|--|-------------------------------|--|-------------|----------------------------------|------------------------|---|--|--|---|---|---------------------|---------------------|---------------------|
| 21.6V | 4.2Ah | EY 7460 LS2S (BLACK EDITION) <ul style="list-style-type: none"> High-performance 4.2Ah Li-ion battery pack Light weight 2.45kg (incl. battery) 13mm high-capacity drill chuck (keyless) Electric speed control Electric brake Reversible Compact body and LED light Incl. second battery pack | <table border="1"> <tr><td>Voltage</td><td>21.6V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>4.2Ah (Li-ion)</td></tr> <tr><td>Charging time (usable / full)</td><td>65 / 85min.</td></tr> <tr><td>Battery</td><td>2 x EY 9L62 B</td></tr> <tr><td>Weight (incl. battery)</td><td>2.45kg</td></tr> <tr><td>Speed at no load (low / high) in min⁻¹ (rpm)</td><td>100-400 / 350-1,500</td></tr> <tr><td>Max. torque (stalling / instant torque)</td><td>42 / 63Nm</td></tr> <tr><td>Clutch stages</td><td>18 + drill position</td></tr> </table> | Voltage | 21.6V | Battery capacity accord. to IEC (technology) | 4.2Ah (Li-ion) | Charging time (usable / full) | 65 / 85min. | Battery | 2 x EY 9L62 B | Weight (incl. battery) | 2.45kg | Speed at no load (low / high) in min ⁻¹ (rpm) | 100-400 / 350-1,500 | Max. torque (stalling / instant torque) | 42 / 63Nm | Clutch stages | 18 + drill position | |
| Voltage | 21.6V | | | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 4.2Ah (Li-ion) | | | | | | | | | | | | | | | | | | | |
| Charging time (usable / full) | 65 / 85min. | | | | | | | | | | | | | | | | | | | |
| Battery | 2 x EY 9L62 B | | | | | | | | | | | | | | | | | | | |
| Weight (incl. battery) | 2.45kg | | | | | | | | | | | | | | | | | | | |
| Speed at no load (low / high) in min ⁻¹ (rpm) | 100-400 / 350-1,500 | | | | | | | | | | | | | | | | | | | |
| Max. torque (stalling / instant torque) | 42 / 63Nm | | | | | | | | | | | | | | | | | | | |
| Clutch stages | 18 + drill position | | | | | | | | | | | | | | | | | | | |
| NEW | 18V | 5.0Ah | EY 74A2 LJ2G <ul style="list-style-type: none"> High-performance 5.0Ah Li-ion battery pack New design high power Brushless motor New 'Speed control function' 'Smooth Start' electronic speed control New ultra hard chuck jaw tips Battery capacity indicator and LED light Ultra compact body 178mm and fresh new 'Carbon' design Incl. second battery pack | <table border="1"> <tr><td>Voltage</td><td>18V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>5.0Ah (Li-ion)</td></tr> <tr><td>Charging time with EY 0L82 B (usable / full)</td><td>65 / 80min.</td></tr> <tr><td>Battery</td><td>2 x EY 9L54 B</td></tr> <tr><td>Weight (incl. battery)</td><td>2.05kg</td></tr> <tr><td>Speed at no load (low / high) in min⁻¹ (rpm)</td><td>20-480 / 70-1,580</td></tr> <tr><td>Max. torque (stalling / instant torque)</td><td>32 / 50Nm</td></tr> <tr><td>Clutch stages</td><td>18 + drill position</td></tr> </table> | Voltage | 18V | Battery capacity accord. to IEC (technology) | 5.0Ah (Li-ion) | Charging time with EY 0L82 B (usable / full) | 65 / 80min. | Battery | 2 x EY 9L54 B | Weight (incl. battery) | 2.05kg | Speed at no load (low / high) in min ⁻¹ (rpm) | 20-480 / 70-1,580 | Max. torque (stalling / instant torque) | 32 / 50Nm | Clutch stages | 18 + drill position |
| Voltage | 18V | | | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 5.0Ah (Li-ion) | | | | | | | | | | | | | | | | | | | |
| Charging time with EY 0L82 B (usable / full) | 65 / 80min. | | | | | | | | | | | | | | | | | | | |
| Battery | 2 x EY 9L54 B | | | | | | | | | | | | | | | | | | | |
| Weight (incl. battery) | 2.05kg | | | | | | | | | | | | | | | | | | | |
| Speed at no load (low / high) in min ⁻¹ (rpm) | 20-480 / 70-1,580 | | | | | | | | | | | | | | | | | | | |
| Max. torque (stalling / instant torque) | 32 / 50Nm | | | | | | | | | | | | | | | | | | | |
| Clutch stages | 18 + drill position | | | | | | | | | | | | | | | | | | | |
| NEW | 18V | 3.0Ah | EY 74A2 PN2G <ul style="list-style-type: none"> High-performance 3.0Ah Li-ion battery pack New design high power Brushless motor New 'Speed control function' 'Smooth Start' electronic speed control New ultra hard chuck jaw tips Battery capacity indicator and LED light Ultra compact body 178mm and new 'Carbon' design Incl. second battery pack | <table border="1"> <tr><td>Voltage</td><td>18V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>3.0Ah (Li-ion)</td></tr> <tr><td>Charging time with EY 0L82 B (usable / full)</td><td>45 / 60min.</td></tr> <tr><td>Battery</td><td>2 x EY 9L53 B</td></tr> <tr><td>Weight (incl. battery)</td><td>1.8kg</td></tr> <tr><td>Speed at no load (low / high) in min⁻¹ (rpm)</td><td>20-480 / 70-1,580</td></tr> <tr><td>Max. torque (stalling / instant torque)</td><td>32 / 50Nm</td></tr> <tr><td>Clutch stages</td><td>18 + drill position</td></tr> </table> | Voltage | 18V | Battery capacity accord. to IEC (technology) | 3.0Ah (Li-ion) | Charging time with EY 0L82 B (usable / full) | 45 / 60min. | Battery | 2 x EY 9L53 B | Weight (incl. battery) | 1.8kg | Speed at no load (low / high) in min ⁻¹ (rpm) | 20-480 / 70-1,580 | Max. torque (stalling / instant torque) | 32 / 50Nm | Clutch stages | 18 + drill position |
| Voltage | 18V | | | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 3.0Ah (Li-ion) | | | | | | | | | | | | | | | | | | | |
| Charging time with EY 0L82 B (usable / full) | 45 / 60min. | | | | | | | | | | | | | | | | | | | |
| Battery | 2 x EY 9L53 B | | | | | | | | | | | | | | | | | | | |
| Weight (incl. battery) | 1.8kg | | | | | | | | | | | | | | | | | | | |
| Speed at no load (low / high) in min ⁻¹ (rpm) | 20-480 / 70-1,580 | | | | | | | | | | | | | | | | | | | |
| Max. torque (stalling / instant torque) | 32 / 50Nm | | | | | | | | | | | | | | | | | | | |
| Clutch stages | 18 + drill position | | | | | | | | | | | | | | | | | | | |
| NEW | 18V | 14.4V | EY 74A2 X <ul style="list-style-type: none"> Such as EY 74A2 LJ2G / PN2G Without battery and charger Compatible with the following batteries 18V: EY 9L54 B, EY 9L53 B, EY 9L52 B, EY 9L51 B, EY 9L50 B 14.4V: EY 9L47 B, EY 9L45 B, EY 9L44 B, EY 9L42 B | <table border="1"> <tr><td>Voltage</td><td>18 / 14.4V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>Depending on battery</td></tr> <tr><td>Charging time with EY 9L54 B (usable / full)</td><td>65 / 80min.</td></tr> <tr><td>Weight (incl. Battery EY 9L54 B)</td><td>2.05kg</td></tr> <tr><td>Speed at no load with EY 9L54 B in rpm (low / high)</td><td>20-480 / 70-1,580</td></tr> <tr><td>Max. torque with EY 9L54 B (stalling / instant torque)</td><td>32 / 50Nm</td></tr> <tr><td>Clutch stages</td><td>18 + drill position</td></tr> </table> | Voltage | 18 / 14.4V | Battery capacity accord. to IEC (technology) | Depending on battery | Charging time with EY 9L54 B (usable / full) | 65 / 80min. | Weight (incl. Battery EY 9L54 B) | 2.05kg | Speed at no load with EY 9L54 B in rpm (low / high) | 20-480 / 70-1,580 | Max. torque with EY 9L54 B (stalling / instant torque) | 32 / 50Nm | Clutch stages | 18 + drill position | | |
| Voltage | 18 / 14.4V | | | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | Depending on battery | | | | | | | | | | | | | | | | | | | |
| Charging time with EY 9L54 B (usable / full) | 65 / 80min. | | | | | | | | | | | | | | | | | | | |
| Weight (incl. Battery EY 9L54 B) | 2.05kg | | | | | | | | | | | | | | | | | | | |
| Speed at no load with EY 9L54 B in rpm (low / high) | 20-480 / 70-1,580 | | | | | | | | | | | | | | | | | | | |
| Max. torque with EY 9L54 B (stalling / instant torque) | 32 / 50Nm | | | | | | | | | | | | | | | | | | | |
| Clutch stages | 18 + drill position | | | | | | | | | | | | | | | | | | | |
| NEW | 18V | 14.4V | EY 74A1 X (BLACK EDITION) <ul style="list-style-type: none"> 13mm high-capacity drill chuck (keyless) Electric speed control Electric brake Compact body and LED light Without battery and charger Compatible with the following batteries 18V: EY 9L54 B, EY 9L53 B, EY 9L52 B, EY 9L51 B, EY 9L50 B 14.4V: EY 9L47 B, EY 9L45 B, EY 9L44 B, EY 9L42 B | <table border="1"> <tr><td>Voltage</td><td>18 / 14.4V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>Depending on battery</td></tr> <tr><td>Charging time with EY 9L54 B (usable / full)</td><td>65 / 80min.</td></tr> <tr><td>Weight (incl. Battery EY 9L54 B)</td><td>1.95kg</td></tr> <tr><td>Speed at no load with EY 9L54 B in rpm (low / high)</td><td>80-600 / 220-1,750</td></tr> <tr><td>Max. torque with EY 9L54 B (stalling / instant torque)</td><td>32 / 42Nm</td></tr> <tr><td>Clutch stages</td><td>18 + drill position</td></tr> </table> | Voltage | 18 / 14.4V | Battery capacity accord. to IEC (technology) | Depending on battery | Charging time with EY 9L54 B (usable / full) | 65 / 80min. | Weight (incl. Battery EY 9L54 B) | 1.95kg | Speed at no load with EY 9L54 B in rpm (low / high) | 80-600 / 220-1,750 | Max. torque with EY 9L54 B (stalling / instant torque) | 32 / 42Nm | Clutch stages | 18 + drill position | | |
| Voltage | 18 / 14.4V | | | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | Depending on battery | | | | | | | | | | | | | | | | | | | |
| Charging time with EY 9L54 B (usable / full) | 65 / 80min. | | | | | | | | | | | | | | | | | | | |
| Weight (incl. Battery EY 9L54 B) | 1.95kg | | | | | | | | | | | | | | | | | | | |
| Speed at no load with EY 9L54 B in rpm (low / high) | 80-600 / 220-1,750 | | | | | | | | | | | | | | | | | | | |
| Max. torque with EY 9L54 B (stalling / instant torque) | 32 / 42Nm | | | | | | | | | | | | | | | | | | | |
| Clutch stages | 18 + drill position | | | | | | | | | | | | | | | | | | | |
| NEW | 18V | 5.0Ah | EY 7450 LJ2S (BLACK EDITION) <ul style="list-style-type: none"> High-performance 5.0Ah Li-ion battery pack Light weight 2.15kg (incl. battery) 13mm high-capacity drill chuck (keyless) Electric speed control Electric brake Reversible Compact body and LED light Incl. second battery pack | <table border="1"> <tr><td>Voltage</td><td>18V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>5.0Ah (Li-ion)</td></tr> <tr><td>Charging time (usable / full)</td><td>65 / 80min.</td></tr> <tr><td>Battery</td><td>2 x EY 9L54 B</td></tr> <tr><td>Weight (incl. battery)</td><td>2.15kg</td></tr> <tr><td>Speed at no load in rpm (low / high)</td><td>50-430 / 160-1.650</td></tr> <tr><td>Max. torque (stalling / instant torque)</td><td>40 / 57Nm</td></tr> <tr><td>Clutch stages</td><td>18 + drill position</td></tr> </table> | Voltage | 18V | Battery capacity accord. to IEC (technology) | 5.0Ah (Li-ion) | Charging time (usable / full) | 65 / 80min. | Battery | 2 x EY 9L54 B | Weight (incl. battery) | 2.15kg | Speed at no load in rpm (low / high) | 50-430 / 160-1.650 | Max. torque (stalling / instant torque) | 40 / 57Nm | Clutch stages | 18 + drill position |
| Voltage | 18V | | | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 5.0Ah (Li-ion) | | | | | | | | | | | | | | | | | | | |
| Charging time (usable / full) | 65 / 80min. | | | | | | | | | | | | | | | | | | | |
| Battery | 2 x EY 9L54 B | | | | | | | | | | | | | | | | | | | |
| Weight (incl. battery) | 2.15kg | | | | | | | | | | | | | | | | | | | |
| Speed at no load in rpm (low / high) | 50-430 / 160-1.650 | | | | | | | | | | | | | | | | | | | |
| Max. torque (stalling / instant torque) | 40 / 57Nm | | | | | | | | | | | | | | | | | | | |
| Clutch stages | 18 + drill position | | | | | | | | | | | | | | | | | | | |
| | 18V | | EY 7450 X (BLACK EDITION) <ul style="list-style-type: none"> Such as EY 7450 LJ2S Without battery and charger Compatible with the following batteries 18V: EY 9L54 B, EY 9L53 B, EY 9L52 B, EY 9L51 B, EY 9L50 B | <table border="1"> <tr><td>Voltage</td><td>18V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>Depending on battery</td></tr> <tr><td>Charging time with EY 9L54 B (usable / full)</td><td>65 / 80min.</td></tr> <tr><td>Weight (incl. Battery EY 9L54 B)</td><td>2.15kg</td></tr> <tr><td>Speed at no load in rpm with EY 9L54 B (low / high)</td><td>50-430 / 160-1.650</td></tr> <tr><td>Max. torque with EY 9L54 B (stalling / instant torque)</td><td>40 / 57Nm</td></tr> <tr><td>Clutch stages</td><td>18 + drill position</td></tr> </table> | Voltage | 18V | Battery capacity accord. to IEC (technology) | Depending on battery | Charging time with EY 9L54 B (usable / full) | 65 / 80min. | Weight (incl. Battery EY 9L54 B) | 2.15kg | Speed at no load in rpm with EY 9L54 B (low / high) | 50-430 / 160-1.650 | Max. torque with EY 9L54 B (stalling / instant torque) | 40 / 57Nm | Clutch stages | 18 + drill position | | |
| Voltage | 18V | | | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | Depending on battery | | | | | | | | | | | | | | | | | | | |
| Charging time with EY 9L54 B (usable / full) | 65 / 80min. | | | | | | | | | | | | | | | | | | | |
| Weight (incl. Battery EY 9L54 B) | 2.15kg | | | | | | | | | | | | | | | | | | | |
| Speed at no load in rpm with EY 9L54 B (low / high) | 50-430 / 160-1.650 | | | | | | | | | | | | | | | | | | | |
| Max. torque with EY 9L54 B (stalling / instant torque) | 40 / 57Nm | | | | | | | | | | | | | | | | | | | |
| Clutch stages | 18 + drill position | | | | | | | | | | | | | | | | | | | |

DRILL & DRIVER

| VOLTAGE (V) / CAPACITY (AH) | | MODEL / FEATURES | | | | | | | | | | | | | | | | | |
|--|----------------------|---|--|---------|-------|--|----------------------|--|-------------|----------------------------------|---------------|---|--------------------|--|--------------------|---|---------------------|---------------|---------------------|
| 14.4V | 4.2Ah | <p>EY 7443 LS2S (BLACK EDITION)</p> <ul style="list-style-type: none"> High-performance 4.2Ah Li-ion battery pack Light weight 1.85kg (incl. battery) AUTO-function 18-stage clutch plus drill position 13mm high-capacity drill chuck (keyless) Electric speed control Electric brake Incl. second battery pack | <table border="1"> <tr><td>Voltage</td><td>14.4V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>4.2Ah (Li-ion)</td></tr> <tr><td>Charging time (usable / full)</td><td>50 / 60min.</td></tr> <tr><td>Battery</td><td>2 x EY 9L45 B</td></tr> <tr><td>Weight (incl. battery)</td><td>1.85kg</td></tr> <tr><td>Speed at no load in rpm (low / high)</td><td>60-400 / 160-1,400</td></tr> <tr><td>Max. torque (stalling / instant torque)</td><td>28 / 41.5Nm</td></tr> <tr><td>Clutch stages</td><td>18 + drill position</td></tr> </table> | Voltage | 14.4V | Battery capacity accord. to IEC (technology) | 4.2Ah (Li-ion) | Charging time (usable / full) | 50 / 60min. | Battery | 2 x EY 9L45 B | Weight (incl. battery) | 1.85kg | Speed at no load in rpm (low / high) | 60-400 / 160-1,400 | Max. torque (stalling / instant torque) | 28 / 41.5Nm | Clutch stages | 18 + drill position |
| Voltage | 14.4V | | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 4.2Ah (Li-ion) | | | | | | | | | | | | | | | | | | |
| Charging time (usable / full) | 50 / 60min. | | | | | | | | | | | | | | | | | | |
| Battery | 2 x EY 9L45 B | | | | | | | | | | | | | | | | | | |
| Weight (incl. battery) | 1.85kg | | | | | | | | | | | | | | | | | | |
| Speed at no load in rpm (low / high) | 60-400 / 160-1,400 | | | | | | | | | | | | | | | | | | |
| Max. torque (stalling / instant torque) | 28 / 41.5Nm | | | | | | | | | | | | | | | | | | |
| Clutch stages | 18 + drill position | | | | | | | | | | | | | | | | | | |
| 14.4V | | <p>EY 7443 X (BLACK EDITION)</p> <ul style="list-style-type: none"> Such as EY 7443 LS2S Without battery and charger Compatible with the following batteries <p>14.4V: EY 9L47 B, EY 9L45 B, EY 9L44 B, EY 9L42 B</p> | <table border="1"> <tr><td>Voltage</td><td>14.4V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>Depending on battery</td></tr> <tr><td>Charging time with EY 9L45 B (usable / full)</td><td>50 / 60min.</td></tr> <tr><td>Weight (incl. Battery EY 9L45 B)</td><td>1.85kg</td></tr> <tr><td>Speed at no load in rpm with EY 9L45 B (low / high)</td><td>60-400 / 160-1,400</td></tr> <tr><td>Max. torque with EY 9L45 B (stalling / instant torque)</td><td>28 / 41.5Nm</td></tr> <tr><td>Clutch stages</td><td>18 + drill position</td></tr> </table> | Voltage | 14.4V | Battery capacity accord. to IEC (technology) | Depending on battery | Charging time with EY 9L45 B (usable / full) | 50 / 60min. | Weight (incl. Battery EY 9L45 B) | 1.85kg | Speed at no load in rpm with EY 9L45 B (low / high) | 60-400 / 160-1,400 | Max. torque with EY 9L45 B (stalling / instant torque) | 28 / 41.5Nm | Clutch stages | 18 + drill position | | |
| Voltage | 14.4V | | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | Depending on battery | | | | | | | | | | | | | | | | | | |
| Charging time with EY 9L45 B (usable / full) | 50 / 60min. | | | | | | | | | | | | | | | | | | |
| Weight (incl. Battery EY 9L45 B) | 1.85kg | | | | | | | | | | | | | | | | | | |
| Speed at no load in rpm with EY 9L45 B (low / high) | 60-400 / 160-1,400 | | | | | | | | | | | | | | | | | | |
| Max. torque with EY 9L45 B (stalling / instant torque) | 28 / 41.5Nm | | | | | | | | | | | | | | | | | | |
| Clutch stages | 18 + drill position | | | | | | | | | | | | | | | | | | |
| 14.4V | 4.2Ah | <p>EY 7441 LS2S</p> <ul style="list-style-type: none"> High-performance 4.2Ah Li-ion battery pack Light weight 1.75kg (incl. battery) 13mm high-capacity drill chuck (keyless) Electric speed control Electric brake Reversible Belt hook and soft grip Incl. second battery pack | <table border="1"> <tr><td>Voltage</td><td>14.4V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>4.2Ah (Li-ion)</td></tr> <tr><td>Charging time (usable / full)</td><td>50 / 60min.</td></tr> <tr><td>Battery</td><td>2 x EY 9L45 B</td></tr> <tr><td>Weight (incl. battery)</td><td>1.75kg</td></tr> <tr><td>Speed at no load in rpm (low / high)</td><td>70-400 / 200-1,400</td></tr> <tr><td>Max. torque (stalling / instant torque)</td><td>28 / 41.5Nm</td></tr> <tr><td>Clutch stages</td><td>18 + drill position</td></tr> </table> | Voltage | 14.4V | Battery capacity accord. to IEC (technology) | 4.2Ah (Li-ion) | Charging time (usable / full) | 50 / 60min. | Battery | 2 x EY 9L45 B | Weight (incl. battery) | 1.75kg | Speed at no load in rpm (low / high) | 70-400 / 200-1,400 | Max. torque (stalling / instant torque) | 28 / 41.5Nm | Clutch stages | 18 + drill position |
| Voltage | 14.4V | | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 4.2Ah (Li-ion) | | | | | | | | | | | | | | | | | | |
| Charging time (usable / full) | 50 / 60min. | | | | | | | | | | | | | | | | | | |
| Battery | 2 x EY 9L45 B | | | | | | | | | | | | | | | | | | |
| Weight (incl. battery) | 1.75kg | | | | | | | | | | | | | | | | | | |
| Speed at no load in rpm (low / high) | 70-400 / 200-1,400 | | | | | | | | | | | | | | | | | | |
| Max. torque (stalling / instant torque) | 28 / 41.5Nm | | | | | | | | | | | | | | | | | | |
| Clutch stages | 18 + drill position | | | | | | | | | | | | | | | | | | |
| 14.4V | | <p>EY 7441 X</p> <ul style="list-style-type: none"> Such as EY 7441 LS2S Without battery and charger Compatible with the following batteries <p>14.4V: EY 9L47 B, EY 9L45 B, EY 9L44 B, EY 9L42 B</p> | <table border="1"> <tr><td>Voltage</td><td>14.4V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>Depending on battery</td></tr> <tr><td>Charging time with EY 9L45 B (usable / full)</td><td>50 / 60min.</td></tr> <tr><td>Weight (incl. Battery EY 9L45 B)</td><td>1.75kg</td></tr> <tr><td>Speed at no load with EY 9L45 B in rpm (low / high)</td><td>70-400 / 200-1,400</td></tr> <tr><td>Max. torque with EY 9L45 B (stalling / instant torque)</td><td>28 / 41.5Nm</td></tr> <tr><td>Clutch stages</td><td>18 + drill position</td></tr> </table> | Voltage | 14.4V | Battery capacity accord. to IEC (technology) | Depending on battery | Charging time with EY 9L45 B (usable / full) | 50 / 60min. | Weight (incl. Battery EY 9L45 B) | 1.75kg | Speed at no load with EY 9L45 B in rpm (low / high) | 70-400 / 200-1,400 | Max. torque with EY 9L45 B (stalling / instant torque) | 28 / 41.5Nm | Clutch stages | 18 + drill position | | |
| Voltage | 14.4V | | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | Depending on battery | | | | | | | | | | | | | | | | | | |
| Charging time with EY 9L45 B (usable / full) | 50 / 60min. | | | | | | | | | | | | | | | | | | |
| Weight (incl. Battery EY 9L45 B) | 1.75kg | | | | | | | | | | | | | | | | | | |
| Speed at no load with EY 9L45 B in rpm (low / high) | 70-400 / 200-1,400 | | | | | | | | | | | | | | | | | | |
| Max. torque with EY 9L45 B (stalling / instant torque) | 28 / 41.5Nm | | | | | | | | | | | | | | | | | | |
| Clutch stages | 18 + drill position | | | | | | | | | | | | | | | | | | |

SCREWDRIVER

| VOLTAGE (V) / CAPACITY (AH) | MODEL / FEATURES | | | | | | | | | | | | | | | | | | |
|--|--|---|---|---------|------|--|----------------|-------------------------------|--------|---------|---------------|------------------------|-------|--------------------------------------|-----------|-----------------------------|------------|---------------|-------------------|
| 3.6V 1.5Ah | EY 7410 LA2S <ul style="list-style-type: none"> 1.5Ah Li-ion battery pack Light weight 0.5kg (incl. battery) 1/4" hex drive 'Auto shut off clutch' with 21 stages Electronic shut off and clutch lock cover LED light Incl. second battery pack |  | <table border="1"> <tr><td>Voltage</td><td>3.6V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>1.5Ah (Li-ion)</td></tr> <tr><td>Charging time (full)</td><td>30min.</td></tr> <tr><td>Battery</td><td>2 x EY 9L10 B</td></tr> <tr><td>Weight (incl. battery)</td><td>0.5kg</td></tr> <tr><td>Speed at no load (low / high) in rpm</td><td>200 / 600</td></tr> <tr><td>Max. torque / clutch stages</td><td>4.4Nm / 21</td></tr> <tr><td>Clutch torque</td><td>Approx. 0.3-2.9Nm</td></tr> </table> | Voltage | 3.6V | Battery capacity accord. to IEC (technology) | 1.5Ah (Li-ion) | Charging time (full) | 30min. | Battery | 2 x EY 9L10 B | Weight (incl. battery) | 0.5kg | Speed at no load (low / high) in rpm | 200 / 600 | Max. torque / clutch stages | 4.4Nm / 21 | Clutch torque | Approx. 0.3-2.9Nm |
| Voltage | 3.6V | | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 1.5Ah (Li-ion) | | | | | | | | | | | | | | | | | | |
| Charging time (full) | 30min. | | | | | | | | | | | | | | | | | | |
| Battery | 2 x EY 9L10 B | | | | | | | | | | | | | | | | | | |
| Weight (incl. battery) | 0.5kg | | | | | | | | | | | | | | | | | | |
| Speed at no load (low / high) in rpm | 200 / 600 | | | | | | | | | | | | | | | | | | |
| Max. torque / clutch stages | 4.4Nm / 21 | | | | | | | | | | | | | | | | | | |
| Clutch torque | Approx. 0.3-2.9Nm | | | | | | | | | | | | | | | | | | |
| 3.6V 1.5Ah | EY 7410 LA1C <ul style="list-style-type: none"> Such as EY 7410 LA2S Without charger and clutch lock cover Incl. one battery pack |  | <table border="1"> <tr><td>Voltage</td><td>3.6V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>1.5Ah (Li-ion)</td></tr> <tr><td>Charging time (usable / full)</td><td>30min.</td></tr> <tr><td>Battery</td><td>1 x EY 9L10 B</td></tr> <tr><td>Weight (incl. battery)</td><td>0.5kg</td></tr> <tr><td>Speed at no load (low / high) in rpm</td><td>200 / 600</td></tr> <tr><td>Max. torque /clutch stages</td><td>4.4Nm / 21</td></tr> <tr><td>Clutch torque</td><td>Approx. 0.3-2.9Nm</td></tr> </table> | Voltage | 3.6V | Battery capacity accord. to IEC (technology) | 1.5Ah (Li-ion) | Charging time (usable / full) | 30min. | Battery | 1 x EY 9L10 B | Weight (incl. battery) | 0.5kg | Speed at no load (low / high) in rpm | 200 / 600 | Max. torque /clutch stages | 4.4Nm / 21 | Clutch torque | Approx. 0.3-2.9Nm |
| Voltage | 3.6V | | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 1.5Ah (Li-ion) | | | | | | | | | | | | | | | | | | |
| Charging time (usable / full) | 30min. | | | | | | | | | | | | | | | | | | |
| Battery | 1 x EY 9L10 B | | | | | | | | | | | | | | | | | | |
| Weight (incl. battery) | 0.5kg | | | | | | | | | | | | | | | | | | |
| Speed at no load (low / high) in rpm | 200 / 600 | | | | | | | | | | | | | | | | | | |
| Max. torque /clutch stages | 4.4Nm / 21 | | | | | | | | | | | | | | | | | | |
| Clutch torque | Approx. 0.3-2.9Nm | | | | | | | | | | | | | | | | | | |
| 3.6V 1.5Ah | EY 7411 LA1S <ul style="list-style-type: none"> 1.5Ah Li-ion battery pack Light weight 0.5kg (incl. battery) Screw count function 1/4" hex drive 'Auto shut off clutch' with 21 stages Electronic shut off LED light Incl. one battery pack |  | <table border="1"> <tr><td>Voltage</td><td>3.6V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>1.5Ah (Li-ion)</td></tr> <tr><td>Charging time (full)</td><td>30min.</td></tr> <tr><td>Battery</td><td>1 x EY 9L10 B</td></tr> <tr><td>Weight (incl. battery)</td><td>0.5kg</td></tr> <tr><td>Speed at no load (low / high) in rpm</td><td>200 / 600</td></tr> <tr><td>Max. torque / clutch stages</td><td>4.4Nm / 21</td></tr> <tr><td>Clutch torque</td><td>Approx. 0.3-2.9Nm</td></tr> </table> | Voltage | 3.6V | Battery capacity accord. to IEC (technology) | 1.5Ah (Li-ion) | Charging time (full) | 30min. | Battery | 1 x EY 9L10 B | Weight (incl. battery) | 0.5kg | Speed at no load (low / high) in rpm | 200 / 600 | Max. torque / clutch stages | 4.4Nm / 21 | Clutch torque | Approx. 0.3-2.9Nm |
| Voltage | 3.6V | | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 1.5Ah (Li-ion) | | | | | | | | | | | | | | | | | | |
| Charging time (full) | 30min. | | | | | | | | | | | | | | | | | | |
| Battery | 1 x EY 9L10 B | | | | | | | | | | | | | | | | | | |
| Weight (incl. battery) | 0.5kg | | | | | | | | | | | | | | | | | | |
| Speed at no load (low / high) in rpm | 200 / 600 | | | | | | | | | | | | | | | | | | |
| Max. torque / clutch stages | 4.4Nm / 21 | | | | | | | | | | | | | | | | | | |
| Clutch torque | Approx. 0.3-2.9Nm | | | | | | | | | | | | | | | | | | |
| 3.6V 1.5Ah | EY 7411 LA1C <ul style="list-style-type: none"> Such as EY 7411 LA2S Without charger Incl. one battery pack |  | <table border="1"> <tr><td>Voltage</td><td>3.6V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>1.5Ah (Li-ion)</td></tr> <tr><td>Charging time (full)</td><td>30min.</td></tr> <tr><td>Battery</td><td>1 x EY 9L10 B</td></tr> <tr><td>Weight (incl. battery)</td><td>0.5kg</td></tr> <tr><td>Speed at no load (low / high) in rpm</td><td>200 / 600</td></tr> <tr><td>Max. torque / clutch stages</td><td>4.4Nm / 21</td></tr> <tr><td>Clutch torque</td><td>Approx. 0.3-2.9Nm</td></tr> </table> | Voltage | 3.6V | Battery capacity accord. to IEC (technology) | 1.5Ah (Li-ion) | Charging time (full) | 30min. | Battery | 1 x EY 9L10 B | Weight (incl. battery) | 0.5kg | Speed at no load (low / high) in rpm | 200 / 600 | Max. torque / clutch stages | 4.4Nm / 21 | Clutch torque | Approx. 0.3-2.9Nm |
| Voltage | 3.6V | | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 1.5Ah (Li-ion) | | | | | | | | | | | | | | | | | | |
| Charging time (full) | 30min. | | | | | | | | | | | | | | | | | | |
| Battery | 1 x EY 9L10 B | | | | | | | | | | | | | | | | | | |
| Weight (incl. battery) | 0.5kg | | | | | | | | | | | | | | | | | | |
| Speed at no load (low / high) in rpm | 200 / 600 | | | | | | | | | | | | | | | | | | |
| Max. torque / clutch stages | 4.4Nm / 21 | | | | | | | | | | | | | | | | | | |
| Clutch torque | Approx. 0.3-2.9Nm | | | | | | | | | | | | | | | | | | |

DRILL & DRIVER AND SCREWDRIVER (LI-ION) – BATTERY CAPACITIES

| VOLTAGE | | | 21.6V | 14.4V | 14.4V |
|------------------------|--|--|---------------|---------------|---------------|
| MODEL | | | EY 7460 LS2S | EY 7443 LS2S | EY 7441 LS2S |
| BATTERY | | | EY 9L62 B(LS) | EY 9L45 B(LS) | EY 9L45 B(LS) |
| Screwing | Wood screws in yellow pine* | Ø 4.1mm x 25mm | 1,700 | 1,200 | 1,200 |
| | Wood screws in yellow pine** | Ø 8mm x 80mm | 570 | - | - |
| | Self-drilling screws in SPC* | Ø 4mm x 13mm t=1.6mm | 1,200 | 750 | 750 |
| Drilling | Holes in plaster board + Plywood/wooding core* | Plaster board 12.5mm + Plywood 12mm Ø 68mm x 24.5mm | 190 | - | - |
| | Holes in plaster board + Plywood** | Plaster board 12.5mm + Plywood 12mm Ø 125mm x 24.5mm | 45 | - | - |
| | Holes in plaster board + Plywood hole saw* | Plaster board 16mm + Plywood 12mm Ø 50mm x 28mm | - | - | - |
| | Holes in SPC* | Ø 13mm t=1.6mm | - | - | - |
| | Holes in SPC/hole saw* | Ø 21mm t=1.6mm | 65 | 25 | 25 |
| | Holes in SPC/hole saw** | Ø 33mm t=1.6mm | 65 | 20 | 20 |
| | Holes in yellow pine* | Ø 18mm x 120mm | 150 | 95 | 95 |
| | Holes in yellow pine* | Ø 21mm x 120mm | - | - | - |
| Holes in yellow pine** | Ø 30mm x 40mm | 210 | 150 | 150 | |

DRILL & DRIVER AND SCREWDRIVER (LI-ION) – BATTERY CAPACITIES

| VOLTAGE | | 18V | 18V | |
|----------|------------------------------|---|---------------|-------------|
| MODEL | | EY 74A2 LJ2G | EY 74A2 PN2G | |
| BATTERY | | EY 9L54 B(LJ) | EY 9L53 B(PN) | |
| Screwing | Holes in yellow pine* | Ø 4.1mm x 25mm | Approx. 1,450 | Approx. 880 |
| | Holes in yellow pine** | Ø 8mm x 80mm | Approx. 390 | Approx. 230 |
| | Self drilling screws in SPC* | Ø 4mm x 13mm t = 1.6mm | Approx. 1,200 | Approx. 710 |
| | Core drill* | Ceramics siding 16mm + Plywood 12mm Ø 65mm x 28mm | Approx. 50 | Approx. 30 |
| | Core drill** | Ceramics siding 16mm + Plywood 12mm Ø 80mm x 28mm | Approx. 30 | Approx. 17 |
| | Wooding core drill* | Plaster board 12.5mm + Plywood 12mm Ø 68mm x 24.5mm | Approx. 90 | Approx. 55 |
| Sawing | Wood hole saw* | Plaster board 12.5mm + Plywood 12mm Ø 50mm, t=24.5mm | Approx. 50 | Approx. 30 |
| | Wood hole saw* | Plaster board 12.5mm + Plywood 16mm Ø 50mm, t=28.5mm | Approx. 50 | Approx. 30 |
| Drilling | Holes in sheet metal* | Ø 21mm t=1.6mm | Approx. 45 | Approx. 25 |
| | Holes in sheet metal** | Ø 25mm t=1.6mm | Approx. 85 | Approx. 50 |
| | Holes in sheet metal** | Ø 33mm t=1.6mm | Approx. 70 | Approx. 40 |
| | Holes in yellow pine* | Ø 18mm x 120mm | Approx. 140 | Approx. 80 |
| | Holes in yellow pine* | Ø 21mm x 120mm | Approx. 140 | Approx. 80 |
| | Holes in yellow pine** | Ø 30mm x 40mm | Approx. 250 | Approx. 150 |

| VOLTAGE | | 3.6V | | |
|----------|----------------------------------|---------------|---------------|-------|
| MODEL | | EY 7410 LA2S | EY 7411 LA1S | |
| BATTERY | | EY 9L10B (LA) | EY 9L10B (LA) | |
| Screwing | Wood screws in soft wood | Ø 3.1 x 13mm | 600 | 600 |
| | Screws in sheet metal (pre-hole) | M5 x 8mm | 1,000 | 1,000 |
| Drilling | Holes in SPC | t=1mm, Ø 2mm | 85 | 85 |

Depending on test condition, the measurement result is sometimes different to that of operation manual. The table shows average values of working capacity per fully charged battery.
* High mode ** Low mode

IMPACT WRENCH & DRIVER

NEW

| VOLTAGE (V) / CAPACITY (AH) | MODEL / FEATURES | | | | | | | | | | | | | | | | | | |
|--|---|---|--|---------|-----|--|----------------------|--|-------------|----------------------------------|---------------|--|-----------|---|-----------|--|-----------|-----------------------------------|-----------|
| 18V 5.0Ah | EY 7552 LJ2S (BLACK EDITION) <ul style="list-style-type: none"> High-performance 5.0Ah Li-ion battery pack Light weight 2.6kg Compact body length: 214mm High power: max. 470Nm New twin hammer block design Electric speed control Electric brake Incl. second battery pack |  | <table border="1"> <tr><td>Voltage</td><td>18V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>5.0Ah (Li-ion)</td></tr> <tr><td>Charging time (usable / full)</td><td>65 / 80min.</td></tr> <tr><td>Battery</td><td>2 x EY 9L54 B</td></tr> <tr><td>Weight (incl. battery)</td><td>2.6kg</td></tr> <tr><td>Speed at no load in min⁻¹ (rpm)</td><td>0 – 1.550</td></tr> <tr><td>Max. torque</td><td>470Nm</td></tr> <tr><td>Impact in min⁻¹ (rpm)</td><td>0 – 2.400</td></tr> </table> | Voltage | 18V | Battery capacity accord. to IEC (technology) | 5.0Ah (Li-ion) | Charging time (usable / full) | 65 / 80min. | Battery | 2 x EY 9L54 B | Weight (incl. battery) | 2.6kg | Speed at no load in min ⁻¹ (rpm) | 0 – 1.550 | Max. torque | 470Nm | Impact in min ⁻¹ (rpm) | 0 – 2.400 |
| Voltage | 18V | | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 5.0Ah (Li-ion) | | | | | | | | | | | | | | | | | | |
| Charging time (usable / full) | 65 / 80min. | | | | | | | | | | | | | | | | | | |
| Battery | 2 x EY 9L54 B | | | | | | | | | | | | | | | | | | |
| Weight (incl. battery) | 2.6kg | | | | | | | | | | | | | | | | | | |
| Speed at no load in min ⁻¹ (rpm) | 0 – 1.550 | | | | | | | | | | | | | | | | | | |
| Max. torque | 470Nm | | | | | | | | | | | | | | | | | | |
| Impact in min ⁻¹ (rpm) | 0 – 2.400 | | | | | | | | | | | | | | | | | | |
| 18V | EY 7552 X (BLACK EDITION) <ul style="list-style-type: none"> Such as EY 7552 LJ2S Without battery and charger Compatible with the following batteries 18V: EY 9L54 B, EY 9L53 B, EY 9L52 B, EY 9L51 B, EY 9L50 B |  | <table border="1"> <tr><td>Voltage</td><td>18V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>Depending on battery</td></tr> <tr><td>Charging time with EY 9L54 B (usable / full)</td><td>65 / 80min.</td></tr> <tr><td>Weight (incl. Battery EY 9L54 B)</td><td>2.6kg</td></tr> <tr><td>Speed at no load with EY 9L54 B in min⁻¹ (rpm)</td><td>0 – 1.550</td></tr> <tr><td>Max. torque with EY 9L54 B</td><td>470Nm</td></tr> <tr><td>Impact with EY 9L54 B in min⁻¹ (rpm)</td><td>0 – 2.400</td></tr> </table> | Voltage | 18V | Battery capacity accord. to IEC (technology) | Depending on battery | Charging time with EY 9L54 B (usable / full) | 65 / 80min. | Weight (incl. Battery EY 9L54 B) | 2.6kg | Speed at no load with EY 9L54 B in min ⁻¹ (rpm) | 0 – 1.550 | Max. torque with EY 9L54 B | 470Nm | Impact with EY 9L54 B in min ⁻¹ (rpm) | 0 – 2.400 | | |
| Voltage | 18V | | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | Depending on battery | | | | | | | | | | | | | | | | | | |
| Charging time with EY 9L54 B (usable / full) | 65 / 80min. | | | | | | | | | | | | | | | | | | |
| Weight (incl. Battery EY 9L54 B) | 2.6kg | | | | | | | | | | | | | | | | | | |
| Speed at no load with EY 9L54 B in min ⁻¹ (rpm) | 0 – 1.550 | | | | | | | | | | | | | | | | | | |
| Max. torque with EY 9L54 B | 470Nm | | | | | | | | | | | | | | | | | | |
| Impact with EY 9L54 B in min ⁻¹ (rpm) | 0 – 2.400 | | | | | | | | | | | | | | | | | | |

IMPACT WRENCH & DRIVER

| VOLTAGE (V) / CAPACITY (AH) | | MODEL / FEATURES | | | | | | | | | | | | | | | | | |
|---|-----------------------------|--|---|---------|------------|--|----------------------|--|-------------|----------------------------------|---------------|---|---------------------------|--|---------------------------|-----------------------------------|-----------------------------|---|-----------------------------|
| NEW | 18V 5.0Ah | EY 75A7 LJ2G <ul style="list-style-type: none"> High-performance 5.0Ah Li-ion battery pack New powerful Brushless Motor New 'Self-Drilling Screw mode' New Hybrid Switch and new 'Carbon' design 3 speed / torque stages (low / middle / high) Battery capacity indicator, belt hook and LED light Ultra compact body 118mm Incl. second battery pack | <table border="1"> <tr><td>Voltage</td><td>18V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>5.0Ah (Li-ion)</td></tr> <tr><td>Charging time with EY 0L82 B (usable / full)</td><td>65 / 80min.</td></tr> <tr><td>Battery</td><td>2 x EY 9L54 B</td></tr> <tr><td>Weight (incl. battery)</td><td>1.7kg</td></tr> <tr><td>Speed at no load in rpm</td><td>0-2,500 / 0-1,450 / 0-950</td></tr> <tr><td>Max. torque (low / middle / high)</td><td>26 / 120 / 160Nm</td></tr> <tr><td>Impact (low / middle / high) in min⁻¹ (rpm)</td><td>0-1,900 / 0-2,900 / 0-3,100</td></tr> </table> | Voltage | 18V | Battery capacity accord. to IEC (technology) | 5.0Ah (Li-ion) | Charging time with EY 0L82 B (usable / full) | 65 / 80min. | Battery | 2 x EY 9L54 B | Weight (incl. battery) | 1.7kg | Speed at no load in rpm | 0-2,500 / 0-1,450 / 0-950 | Max. torque (low / middle / high) | 26 / 120 / 160Nm | Impact (low / middle / high) in min ⁻¹ (rpm) | 0-1,900 / 0-2,900 / 0-3,100 |
| Voltage | 18V | | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 5.0Ah (Li-ion) | | | | | | | | | | | | | | | | | | |
| Charging time with EY 0L82 B (usable / full) | 65 / 80min. | | | | | | | | | | | | | | | | | | |
| Battery | 2 x EY 9L54 B | | | | | | | | | | | | | | | | | | |
| Weight (incl. battery) | 1.7kg | | | | | | | | | | | | | | | | | | |
| Speed at no load in rpm | 0-2,500 / 0-1,450 / 0-950 | | | | | | | | | | | | | | | | | | |
| Max. torque (low / middle / high) | 26 / 120 / 160Nm | | | | | | | | | | | | | | | | | | |
| Impact (low / middle / high) in min ⁻¹ (rpm) | 0-1,900 / 0-2,900 / 0-3,100 | | | | | | | | | | | | | | | | | | |
| NEW | 18V 3.0Ah | EY 75A7 PN2G <ul style="list-style-type: none"> High-performance 3.0Ah Li-ion battery pack New powerful Brushless Motor New 'Self-Drilling Screw mode' New Hybrid Switch and new 'Carbon' design 3 speed / torque stages (low / middle / high) Battery capacity indicator, belt hook and LED light Ultra compact body 118mm Incl. second battery pack | <table border="1"> <tr><td>Voltage</td><td>18V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>3.0Ah (Li-ion)</td></tr> <tr><td>Charging time with EY 0L82 B (usable / full)</td><td>45 / 60min.</td></tr> <tr><td>Battery</td><td>2 x EY 9L53 B</td></tr> <tr><td>Weight (incl. battery)</td><td>1.5kg</td></tr> <tr><td>Speed at no load in rpm</td><td>0-2,500 / 0-1,450 / 0-950</td></tr> <tr><td>Max. torque (low / middle / high)</td><td>26 / 120 / 160Nm</td></tr> <tr><td>Impact (low / middle / high) in min⁻¹ (rpm)</td><td>0-1,900 / 0-2,900 / 0-3,100</td></tr> </table> | Voltage | 18V | Battery capacity accord. to IEC (technology) | 3.0Ah (Li-ion) | Charging time with EY 0L82 B (usable / full) | 45 / 60min. | Battery | 2 x EY 9L53 B | Weight (incl. battery) | 1.5kg | Speed at no load in rpm | 0-2,500 / 0-1,450 / 0-950 | Max. torque (low / middle / high) | 26 / 120 / 160Nm | Impact (low / middle / high) in min ⁻¹ (rpm) | 0-1,900 / 0-2,900 / 0-3,100 |
| Voltage | 18V | | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 3.0Ah (Li-ion) | | | | | | | | | | | | | | | | | | |
| Charging time with EY 0L82 B (usable / full) | 45 / 60min. | | | | | | | | | | | | | | | | | | |
| Battery | 2 x EY 9L53 B | | | | | | | | | | | | | | | | | | |
| Weight (incl. battery) | 1.5kg | | | | | | | | | | | | | | | | | | |
| Speed at no load in rpm | 0-2,500 / 0-1,450 / 0-950 | | | | | | | | | | | | | | | | | | |
| Max. torque (low / middle / high) | 26 / 120 / 160Nm | | | | | | | | | | | | | | | | | | |
| Impact (low / middle / high) in min ⁻¹ (rpm) | 0-1,900 / 0-2,900 / 0-3,100 | | | | | | | | | | | | | | | | | | |
| NEW | 18V 14.4V | EY 75A7 X <ul style="list-style-type: none"> Such as EY 75A7 LJ2G / PN2G Without battery and charger Compatible with the following batteries <p>18V: EY 9L54 B, EY 9L53 B, EY 9L52 B, EY 9L51 B, EY 9L50 B 14.4V: EY 9L47 B, EY 9L45 B, EY 9L44 B, EY 9L42 B</p> | <table border="1"> <tr><td>Voltage</td><td>18 / 14.4V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>Depending on battery</td></tr> <tr><td>Charging time with EY 9L54 B (usable / full)</td><td>65 / 80min.</td></tr> <tr><td>Weight (incl. Battery EY 9L54 B)</td><td>1.7kg</td></tr> <tr><td>Speed at no load with EY 9L54 B in rpm (low / high)</td><td>0-2,500 / 0-1,450 / 0-950</td></tr> <tr><td>Max. torque with EY 9L54 B (stalling / instant torque)</td><td>26 / 120 / 160Nm</td></tr> <tr><td>Clutch stages</td><td>0-1,900 / 0-2,900 / 0-3,100</td></tr> </table> | Voltage | 18 / 14.4V | Battery capacity accord. to IEC (technology) | Depending on battery | Charging time with EY 9L54 B (usable / full) | 65 / 80min. | Weight (incl. Battery EY 9L54 B) | 1.7kg | Speed at no load with EY 9L54 B in rpm (low / high) | 0-2,500 / 0-1,450 / 0-950 | Max. torque with EY 9L54 B (stalling / instant torque) | 26 / 120 / 160Nm | Clutch stages | 0-1,900 / 0-2,900 / 0-3,100 | | |
| Voltage | 18 / 14.4V | | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | Depending on battery | | | | | | | | | | | | | | | | | | |
| Charging time with EY 9L54 B (usable / full) | 65 / 80min. | | | | | | | | | | | | | | | | | | |
| Weight (incl. Battery EY 9L54 B) | 1.7kg | | | | | | | | | | | | | | | | | | |
| Speed at no load with EY 9L54 B in rpm (low / high) | 0-2,500 / 0-1,450 / 0-950 | | | | | | | | | | | | | | | | | | |
| Max. torque with EY 9L54 B (stalling / instant torque) | 26 / 120 / 160Nm | | | | | | | | | | | | | | | | | | |
| Clutch stages | 0-1,900 / 0-2,900 / 0-3,100 | | | | | | | | | | | | | | | | | | |
| NEW | 18V 5.0Ah | EY 75A2 LJ2G (BLACK EDITION) <ul style="list-style-type: none"> High-performance 5.0Ah Li-ion battery pack Light weight 1.65kg (incl. battery) 1/2" square drive Brushless motor and hybrid switch Electric speed control Electric brake Belt hook and LED light Incl. second battery pack | <table border="1"> <tr><td>Voltage</td><td>18V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>5.0Ah (Li-ion)</td></tr> <tr><td>Charging time (usable / full)</td><td>65 / 80min.</td></tr> <tr><td>Battery</td><td>2 x EY 9L54 B</td></tr> <tr><td>Weight (incl. battery)</td><td>1.65kg</td></tr> <tr><td>Speed at no load in rpm</td><td>0 - 2,300</td></tr> <tr><td>Max. torque (low / middle / high)</td><td>50 / 140 / 205Nm</td></tr> <tr><td>Impact (low / middle / high)</td><td>3</td></tr> </table> | Voltage | 18V | Battery capacity accord. to IEC (technology) | 5.0Ah (Li-ion) | Charging time (usable / full) | 65 / 80min. | Battery | 2 x EY 9L54 B | Weight (incl. battery) | 1.65kg | Speed at no load in rpm | 0 - 2,300 | Max. torque (low / middle / high) | 50 / 140 / 205Nm | Impact (low / middle / high) | 3 |
| Voltage | 18V | | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 5.0Ah (Li-ion) | | | | | | | | | | | | | | | | | | |
| Charging time (usable / full) | 65 / 80min. | | | | | | | | | | | | | | | | | | |
| Battery | 2 x EY 9L54 B | | | | | | | | | | | | | | | | | | |
| Weight (incl. battery) | 1.65kg | | | | | | | | | | | | | | | | | | |
| Speed at no load in rpm | 0 - 2,300 | | | | | | | | | | | | | | | | | | |
| Max. torque (low / middle / high) | 50 / 140 / 205Nm | | | | | | | | | | | | | | | | | | |
| Impact (low / middle / high) | 3 | | | | | | | | | | | | | | | | | | |
| NEW | 18V 3.0Ah | EY 75A2 PN2G (BLACK EDITION) <ul style="list-style-type: none"> High-performance 3.00Ah Li-ion battery pack Light weight 1.55kg (incl. battery) 1/2" square drive Brushless motor and hybrid switch Electric speed control Electric brake Belt hook and LED light Incl. second battery pack | <table border="1"> <tr><td>Voltage</td><td>18V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>3.0Ah (Li-ion)</td></tr> <tr><td>Charging time (usable / full)</td><td>45 / 60min.</td></tr> <tr><td>Battery</td><td>2 x EY 9L53 B</td></tr> <tr><td>Weight (incl. battery)</td><td>1.55kg</td></tr> <tr><td>Speed at no load in rpm</td><td>0 - 2,300</td></tr> <tr><td>Max. torque (low / middle / high)</td><td>50 / 140 / 205Nm</td></tr> <tr><td>Impact (low / middle / high)</td><td>3</td></tr> </table> | Voltage | 18V | Battery capacity accord. to IEC (technology) | 3.0Ah (Li-ion) | Charging time (usable / full) | 45 / 60min. | Battery | 2 x EY 9L53 B | Weight (incl. battery) | 1.55kg | Speed at no load in rpm | 0 - 2,300 | Max. torque (low / middle / high) | 50 / 140 / 205Nm | Impact (low / middle / high) | 3 |
| Voltage | 18V | | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 3.0Ah (Li-ion) | | | | | | | | | | | | | | | | | | |
| Charging time (usable / full) | 45 / 60min. | | | | | | | | | | | | | | | | | | |
| Battery | 2 x EY 9L53 B | | | | | | | | | | | | | | | | | | |
| Weight (incl. battery) | 1.55kg | | | | | | | | | | | | | | | | | | |
| Speed at no load in rpm | 0 - 2,300 | | | | | | | | | | | | | | | | | | |
| Max. torque (low / middle / high) | 50 / 140 / 205Nm | | | | | | | | | | | | | | | | | | |
| Impact (low / middle / high) | 3 | | | | | | | | | | | | | | | | | | |
| | 18V 14.4V | EY 75A2 X (BLACK EDITION) <ul style="list-style-type: none"> Such as EY 75A2 LJ2G / PN2G Without battery and charger Compatible with the following batteries <p>18V: EY 9L54 B, EY 9L53 B, EY 9L52 B, EY 9L51 B, EY 9L50 B 14.4V: EY 9L47 B, EY 9L45 B, EY 9L44 B, EY 9L42 B</p> | <table border="1"> <tr><td>Voltage</td><td>18 / 14.4V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>Depending on battery</td></tr> <tr><td>Charging time with EY 9L54 B (usable / full)</td><td>65 / 80min.</td></tr> <tr><td>Weight (incl. Battery EY 9L54 B)</td><td>1.65kg</td></tr> <tr><td>Speed at no load with EY 9L54 B in rpm</td><td>0 - 2,300</td></tr> <tr><td>Max. torque with EY 9L54 B (low / middle / high)</td><td>50 / 140 / 205Nm</td></tr> <tr><td>Impact (low / middle / high)</td><td>3</td></tr> </table> | Voltage | 18 / 14.4V | Battery capacity accord. to IEC (technology) | Depending on battery | Charging time with EY 9L54 B (usable / full) | 65 / 80min. | Weight (incl. Battery EY 9L54 B) | 1.65kg | Speed at no load with EY 9L54 B in rpm | 0 - 2,300 | Max. torque with EY 9L54 B (low / middle / high) | 50 / 140 / 205Nm | Impact (low / middle / high) | 3 | | |
| Voltage | 18 / 14.4V | | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | Depending on battery | | | | | | | | | | | | | | | | | | |
| Charging time with EY 9L54 B (usable / full) | 65 / 80min. | | | | | | | | | | | | | | | | | | |
| Weight (incl. Battery EY 9L54 B) | 1.65kg | | | | | | | | | | | | | | | | | | |
| Speed at no load with EY 9L54 B in rpm | 0 - 2,300 | | | | | | | | | | | | | | | | | | |
| Max. torque with EY 9L54 B (low / middle / high) | 50 / 140 / 205Nm | | | | | | | | | | | | | | | | | | |
| Impact (low / middle / high) | 3 | | | | | | | | | | | | | | | | | | |
| | 14.4V 4.2Ah | EY 7549 LS2S (BLACK EDITION) <ul style="list-style-type: none"> High-performance 4.2Ah Li-ion battery pack Light weight 1.85kg (incl. battery) Multifunction: Drill, Screwdriver, Impact Driver, Impact Wrench Two modes: impact mode and drilldriver mode Quick change 1/4" hex adaptor Drilldriver mode with 21 stage clutch plus drill position Incl. second battery pack | <table border="1"> <tr><td>Voltage</td><td>14.4V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>4.2Ah (Li-ion)</td></tr> <tr><td>Charging time (usable / full)</td><td>50 / 60min.</td></tr> <tr><td>Battery</td><td>2 x EY 9L45 B</td></tr> <tr><td>Weight (incl. battery)</td><td>1.85kg</td></tr> <tr><td>Speed at no load in rpm</td><td>380 - 1,200</td></tr> <tr><td>Max. torque (low / high)</td><td>9 / 26Nm</td></tr> <tr><td>Clutch torque</td><td>0,7 - 4,4Nm</td></tr> </table> | Voltage | 14.4V | Battery capacity accord. to IEC (technology) | 4.2Ah (Li-ion) | Charging time (usable / full) | 50 / 60min. | Battery | 2 x EY 9L45 B | Weight (incl. battery) | 1.85kg | Speed at no load in rpm | 380 - 1,200 | Max. torque (low / high) | 9 / 26Nm | Clutch torque | 0,7 - 4,4Nm |
| Voltage | 14.4V | | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 4.2Ah (Li-ion) | | | | | | | | | | | | | | | | | | |
| Charging time (usable / full) | 50 / 60min. | | | | | | | | | | | | | | | | | | |
| Battery | 2 x EY 9L45 B | | | | | | | | | | | | | | | | | | |
| Weight (incl. battery) | 1.85kg | | | | | | | | | | | | | | | | | | |
| Speed at no load in rpm | 380 - 1,200 | | | | | | | | | | | | | | | | | | |
| Max. torque (low / high) | 9 / 26Nm | | | | | | | | | | | | | | | | | | |
| Clutch torque | 0,7 - 4,4Nm | | | | | | | | | | | | | | | | | | |

IMPACT WRENCH & DRIVER

| VOLTAGE (V) / CAPACITY (AH) | MODEL / FEATURES | | | | | | | | | | | | | | | |
|--|--|---|---------|-------|--|----------------------|--|-------------|----------------------------------|--------|--|-------------|---|----------|---------------|-------------|
| 14.4V | EY 7549 X (BLACK EDITION) | | | | | | | | | | | | | | | |
|  TOUGH TOOL IP™ | <ul style="list-style-type: none"> Such as EY 7549 LS2S Without battery and charger Compatible with the following batteries 14.4V: EY 9L47 B, EY 9L45 B, EY 9L44 B, EY 9L42 B | <table border="1"> <tr> <td>Voltage</td> <td>14.4V</td> </tr> <tr> <td>Battery capacity accord. to IEC (technology)</td> <td>Depending on battery</td> </tr> <tr> <td>Charging time with EY 9L45 B (usable / full)</td> <td>50 / 60min.</td> </tr> <tr> <td>Weight (incl. Battery EY 9L45 B)</td> <td>1.85kg</td> </tr> <tr> <td>Speed at no load with EY 9L45 B in rpm</td> <td>380 – 1,200</td> </tr> <tr> <td>Max. torque with EY 9L45 B (low / high)</td> <td>9 / 26Nm</td> </tr> <tr> <td>Clutch torque</td> <td>0,7 – 4,4Nm</td> </tr> </table> | Voltage | 14.4V | Battery capacity accord. to IEC (technology) | Depending on battery | Charging time with EY 9L45 B (usable / full) | 50 / 60min. | Weight (incl. Battery EY 9L45 B) | 1.85kg | Speed at no load with EY 9L45 B in rpm | 380 – 1,200 | Max. torque with EY 9L45 B (low / high) | 9 / 26Nm | Clutch torque | 0,7 – 4,4Nm |
| | Voltage | 14.4V | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | Depending on battery | | | | | | | | | | | | | | | |
| Charging time with EY 9L45 B (usable / full) | 50 / 60min. | | | | | | | | | | | | | | | |
| Weight (incl. Battery EY 9L45 B) | 1.85kg | | | | | | | | | | | | | | | |
| Speed at no load with EY 9L45 B in rpm | 380 – 1,200 | | | | | | | | | | | | | | | |
| Max. torque with EY 9L45 B (low / high) | 9 / 26Nm | | | | | | | | | | | | | | | |
| Clutch torque | 0,7 – 4,4Nm | | | | | | | | | | | | | | | |

IMPACT WRENCH & DRIVER – BATTERY CAPACITIES

| VOLTAGE | | | | 18V |
|---------------------|----------------------------|-------------------|--------------------------|--------------|
| MODEL | | | | EY 7552 LJ2S |
| BATTERY | | | | EY9L54 B(LJ) |
| Screwing | SPAX Screws in yellow pine | Ø 8mm x 80mm | | Approx. 230 |
| | Standard tensile bolt | M12 x 25mm t=10mm | 1 second | Approx. 720 |
| Bolting application | Standard tensile bolt | M16 x 25mm t=10mm | 2 seconds | Approx. 320 |
| | Standard tensile bolt | M16 x 25mm t=10mm | 3 seconds with extension | Approx. 200 |
| | High tensile bolt | M16 x 25mm t=10mm | 2 seconds | Approx. 330 |
| | High tensile bolt | M20 x 25mm t=10mm | 2,5 seconds | Approx. 280 |
| | High tensile bolt | M24 x 25mm t=10mm | 3 seconds | - |

| VOLTAGE | | | | 18V | |
|---------------------|-----------------------------|----------------------|--|---------------|---------------|
| MODEL | | | | EY 75A7 LJ2G | EY 75A7 PN2G |
| BATTERY | | | | EY 9L54 B(LJ) | EY 9L53 B(PN) |
| Screwing | Wood screws in yellow pine | Ø 4.2mm x 75mm | | Approx. 700 | Approx. 420 |
| | Self-drilling screws in SPC | Ø 4mm x 13mm t=1.6mm | | Approx. 980 | Approx. 590 |
| Bolting application | Standard tensile bolt | M16 x 25mm t=10mm | | Approx. 1,150 | Approx. 680 |
| | Standard tensile bolt | M12 x 25mm t=10mm | | Approx. 2,700 | Approx. 1.600 |
| | High tensile bolt | M12 x 25mm t=10mm | | Approx. 360 | Approx. 220 |

| VOLTAGE | | | | 18V | |
|---------------------|------------------------------|----------------------|--|---------------|---------------|
| MODEL | | | | EY 75A2 LJ2G | EY 75A2 PN2G |
| BATTERY | | | | EY 9L54 B(LJ) | EY 9L53 B(PN) |
| Screwing | Wood screws in yellow pine* | Ø 4.2mm x 75mm | | Approx. 620 | Approx. 370 |
| | Wood screws in yellow pine* | Ø 5.2mm x 120mm | | Approx. 140 | Approx. 85 |
| | Self-drilling screws in SPC* | Ø 4mm x 13mm t=1.6mm | | Approx. 1,050 | Approx. 640 |
| Bolting application | Standard tensile bolt* | M16 x 25mm t=10mm | | Approx. 1,150 | Approx. 680 |
| | Standard tensile bolt* | M14 x 25mm t=10mm | | Approx. 1,230 | Approx. 740 |
| | High tensile bolt* | M12 x 25mm t=10mm | | Approx. 400 | Approx. 240 |

MULTI-IMPACT & DRILL DRIVER – BATTERY CAPACITIES

| VOLTAGE | | | | 14.4V |
|-------------|-----------------------------|------------------------|--|---------------|
| MODEL | | | | EY 7549 LS2S |
| BATTERY | | | | EY 9L45 B(LS) |
| DD mode | Holes in yellow pine* | Ø 18mm x 120mm | | 90 |
| Impact mode | Self drilling screws in SPC | Ø 21mm t=1.6mm | | 19 |
| | HUS | Ø 6mm x 60 in concrete | | 450 |
| Bolting | High tensile bolt | M12 x 25mm t=10mm | | 200 |

Depending on test condition, the measurement result is sometimes different to that of operation manual. The table shows average values of working capacity per fully charged battery.
 * High mode ** Low mode

TWO PIECE SETS

| VOLTAGE (V) / CAPACITY (Ah) | | MODEL / FEATURES | | | | | | | | | | | | | | | | | |
|--|------------------|--|---|---------|-------|--|----------------|-------------------------------|-------------|----------------|-----------|---------------|-----------|---------|---------------|---------|-----------|---------|------------------|
| NEW | 18V 5.0Ah | EYC 215 LJ2G Two Piece Set <ul style="list-style-type: none"> ■ Drill & Driver EY 74A2 X ■ Impact Driver EY 75A7 X ■ 2 x battery EY 9L54 B with 5.0Ah ■ 1 x charger EY 0L82 B | <table border="1"> <tr><td>Voltage</td><td>18V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>5.0Ah (Li-ion)</td></tr> <tr><td>Charging time (usable / full)</td><td>65 / 80min.</td></tr> <tr><td>Drill & Driver</td><td>EY 74A2 X</td></tr> <tr><td>Impact Driver</td><td>EY 75A7 X</td></tr> <tr><td>Battery</td><td>2 x EY 9L54 B</td></tr> <tr><td>Charger</td><td>EY 0L82 B</td></tr> </table> | Voltage | 18V | Battery capacity accord. to IEC (technology) | 5.0Ah (Li-ion) | Charging time (usable / full) | 65 / 80min. | Drill & Driver | EY 74A2 X | Impact Driver | EY 75A7 X | Battery | 2 x EY 9L54 B | Charger | EY 0L82 B | | |
| Voltage | 18V | | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 5.0Ah (Li-ion) | | | | | | | | | | | | | | | | | | |
| Charging time (usable / full) | 65 / 80min. | | | | | | | | | | | | | | | | | | |
| Drill & Driver | EY 74A2 X | | | | | | | | | | | | | | | | | | |
| Impact Driver | EY 75A7 X | | | | | | | | | | | | | | | | | | |
| Battery | 2 x EY 9L54 B | | | | | | | | | | | | | | | | | | |
| Charger | EY 0L82 B | | | | | | | | | | | | | | | | | | |
| NEW | 18V 3.0Ah | EYC 215 PN2G Two Piece Set <ul style="list-style-type: none"> ■ Drill & Driver EY 74A2 X ■ Impact Driver EY 75A7 X ■ 2 x battery EY 9L53 B with 3.0Ah ■ 1 x charger EY 0L82 B | <table border="1"> <tr><td>Voltage</td><td>18V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>3.0Ah (Li-ion)</td></tr> <tr><td>Charging time (usable / full)</td><td>45 / 60min.</td></tr> <tr><td>Drill & Driver</td><td>EY 74A2 X</td></tr> <tr><td>Impact Driver</td><td>EY 75A7 X</td></tr> <tr><td>Battery</td><td>2 x EY 9L53 B</td></tr> <tr><td>Charger</td><td>EY 0L82 B</td></tr> </table> | Voltage | 18V | Battery capacity accord. to IEC (technology) | 3.0Ah (Li-ion) | Charging time (usable / full) | 45 / 60min. | Drill & Driver | EY 74A2 X | Impact Driver | EY 75A7 X | Battery | 2 x EY 9L53 B | Charger | EY 0L82 B | | |
| Voltage | 18V | | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 3.0Ah (Li-ion) | | | | | | | | | | | | | | | | | | |
| Charging time (usable / full) | 45 / 60min. | | | | | | | | | | | | | | | | | | |
| Drill & Driver | EY 74A2 X | | | | | | | | | | | | | | | | | | |
| Impact Driver | EY 75A7 X | | | | | | | | | | | | | | | | | | |
| Battery | 2 x EY 9L53 B | | | | | | | | | | | | | | | | | | |
| Charger | EY 0L82 B | | | | | | | | | | | | | | | | | | |
| NEW | 14.4V 4.2Ah | EYC 215 LS2F Two Piece Set <ul style="list-style-type: none"> ■ Drill & Driver EY 74A2 X ■ Impact Driver EY 75A7 X ■ 2 x battery EY 9L45 B with 4.2Ah ■ 1 x charger EY 0L82 B | <table border="1"> <tr><td>Voltage</td><td>14.4V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>4.2Ah (Li-ion)</td></tr> <tr><td>Charging time (usable / full)</td><td>50 / 60min.</td></tr> <tr><td>Drill & Driver</td><td>EY 74A2 X</td></tr> <tr><td>Impact Driver</td><td>EY 75A7 X</td></tr> <tr><td>Battery</td><td>2 x EY 9L45 B</td></tr> <tr><td>Charger</td><td>EY 0L82 B</td></tr> </table> | Voltage | 14.4V | Battery capacity accord. to IEC (technology) | 4.2Ah (Li-ion) | Charging time (usable / full) | 50 / 60min. | Drill & Driver | EY 74A2 X | Impact Driver | EY 75A7 X | Battery | 2 x EY 9L45 B | Charger | EY 0L82 B | | |
| Voltage | 14.4V | | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 4.2Ah (Li-ion) | | | | | | | | | | | | | | | | | | |
| Charging time (usable / full) | 50 / 60min. | | | | | | | | | | | | | | | | | | |
| Drill & Driver | EY 74A2 X | | | | | | | | | | | | | | | | | | |
| Impact Driver | EY 75A7 X | | | | | | | | | | | | | | | | | | |
| Battery | 2 x EY 9L45 B | | | | | | | | | | | | | | | | | | |
| Charger | EY 0L82 B | | | | | | | | | | | | | | | | | | |
| NEW | 18V 5.0Ah | EYC 216 LJ2G Two Piece Set <ul style="list-style-type: none"> ■ Drill & Driver EY 74A2 X ■ Impact Wrench EY 75A2 X ■ 2 x battery EY 9L54 B with 5.0Ah ■ 1 x charger EY 0L82 B ■ Incl. adapter EY 9 HX 111 E32 | <table border="1"> <tr><td>Voltage</td><td>18V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>5.0Ah (Li-ion)</td></tr> <tr><td>Charging time (usable / full)</td><td>65 / 80min.</td></tr> <tr><td>Drill & Driver</td><td>EY 74A2 X</td></tr> <tr><td>Impact Wrench</td><td>EY 75A2 X</td></tr> <tr><td>Battery</td><td>2 x EY 9L54 B</td></tr> <tr><td>Charger</td><td>EY 0L82 B</td></tr> <tr><td>Adapter</td><td>EY 9 HX 111 E 32</td></tr> </table> | Voltage | 18V | Battery capacity accord. to IEC (technology) | 5.0Ah (Li-ion) | Charging time (usable / full) | 65 / 80min. | Drill & Driver | EY 74A2 X | Impact Wrench | EY 75A2 X | Battery | 2 x EY 9L54 B | Charger | EY 0L82 B | Adapter | EY 9 HX 111 E 32 |
| Voltage | 18V | | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 5.0Ah (Li-ion) | | | | | | | | | | | | | | | | | | |
| Charging time (usable / full) | 65 / 80min. | | | | | | | | | | | | | | | | | | |
| Drill & Driver | EY 74A2 X | | | | | | | | | | | | | | | | | | |
| Impact Wrench | EY 75A2 X | | | | | | | | | | | | | | | | | | |
| Battery | 2 x EY 9L54 B | | | | | | | | | | | | | | | | | | |
| Charger | EY 0L82 B | | | | | | | | | | | | | | | | | | |
| Adapter | EY 9 HX 111 E 32 | | | | | | | | | | | | | | | | | | |
| NEW | 18V 3.0Ah | EYC 216 PN2G Two Piece Set <ul style="list-style-type: none"> ■ Drill & Driver EY 74A2 X ■ Impact Wrench EY 75A2 X ■ 2 x battery EY 9L53 B with 3.0Ah ■ 1 x charger EY 0L82 B ■ Incl. adapter EY 9 HX 111 E32 | <table border="1"> <tr><td>Voltage</td><td>18V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>3.0Ah (Li-ion)</td></tr> <tr><td>Charging time (usable / full)</td><td>45 / 60min.</td></tr> <tr><td>Drill & Driver</td><td>EY 74A2 X</td></tr> <tr><td>Impact Wrench</td><td>EY 75A2 X</td></tr> <tr><td>Battery</td><td>2 x EY 9L53 B</td></tr> <tr><td>Charger</td><td>EY 0L82 B</td></tr> <tr><td>Adapter</td><td>EY 9 HX 111 E 32</td></tr> </table> | Voltage | 18V | Battery capacity accord. to IEC (technology) | 3.0Ah (Li-ion) | Charging time (usable / full) | 45 / 60min. | Drill & Driver | EY 74A2 X | Impact Wrench | EY 75A2 X | Battery | 2 x EY 9L53 B | Charger | EY 0L82 B | Adapter | EY 9 HX 111 E 32 |
| Voltage | 18V | | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 3.0Ah (Li-ion) | | | | | | | | | | | | | | | | | | |
| Charging time (usable / full) | 45 / 60min. | | | | | | | | | | | | | | | | | | |
| Drill & Driver | EY 74A2 X | | | | | | | | | | | | | | | | | | |
| Impact Wrench | EY 75A2 X | | | | | | | | | | | | | | | | | | |
| Battery | 2 x EY 9L53 B | | | | | | | | | | | | | | | | | | |
| Charger | EY 0L82 B | | | | | | | | | | | | | | | | | | |
| Adapter | EY 9 HX 111 E 32 | | | | | | | | | | | | | | | | | | |
| NEW | 14.4V 4.2Ah | EYC 216 LS2F Two Piece Set <ul style="list-style-type: none"> ■ Drill & Driver EY 74A2 X ■ Impact Wrench EY 75A2 X ■ 2 x battery EY 9L45 B with 4.2Ah ■ 1 x charger EY 0L82 B ■ Incl. adapter EY 9 HX 111 E32 | <table border="1"> <tr><td>Voltage</td><td>14.4V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>4.2Ah (Li-ion)</td></tr> <tr><td>Charging time (usable / full)</td><td>50 / 60min.</td></tr> <tr><td>Drill & Driver</td><td>EY 74A2 X</td></tr> <tr><td>Impact Wrench</td><td>EY 75A2 X</td></tr> <tr><td>Battery</td><td>2 x EY 9L45 B</td></tr> <tr><td>Charger</td><td>EY 0L82 B</td></tr> <tr><td>Adapter</td><td>EY 9 HX 111 E 32</td></tr> </table> | Voltage | 14.4V | Battery capacity accord. to IEC (technology) | 4.2Ah (Li-ion) | Charging time (usable / full) | 50 / 60min. | Drill & Driver | EY 74A2 X | Impact Wrench | EY 75A2 X | Battery | 2 x EY 9L45 B | Charger | EY 0L82 B | Adapter | EY 9 HX 111 E 32 |
| Voltage | 14.4V | | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 4.2Ah (Li-ion) | | | | | | | | | | | | | | | | | | |
| Charging time (usable / full) | 50 / 60min. | | | | | | | | | | | | | | | | | | |
| Drill & Driver | EY 74A2 X | | | | | | | | | | | | | | | | | | |
| Impact Wrench | EY 75A2 X | | | | | | | | | | | | | | | | | | |
| Battery | 2 x EY 9L45 B | | | | | | | | | | | | | | | | | | |
| Charger | EY 0L82 B | | | | | | | | | | | | | | | | | | |
| Adapter | EY 9 HX 111 E 32 | | | | | | | | | | | | | | | | | | |
| NEW | 18V 5.0Ah | EYC 217 LJ2G Two Piece Set <ul style="list-style-type: none"> ■ Drill Driver EY 79A2 X ■ Impact Driver EY 75A7 X ■ 2 x battery EY 9L54 B with 5.0Ah ■ 1 x charger EY 0L82 B | <table border="1"> <tr><td>Voltage</td><td>18V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>5.0Ah (Li-ion)</td></tr> <tr><td>Charging time (usable / full)</td><td>65 / 80min.</td></tr> <tr><td>Drill & Driver</td><td>EY 79A2 X</td></tr> <tr><td>Impact Driver</td><td>EY 75A7 X</td></tr> <tr><td>Battery</td><td>2 x EY 9L54 B</td></tr> <tr><td>Charger</td><td>EY 0L82 B</td></tr> </table> | Voltage | 18V | Battery capacity accord. to IEC (technology) | 5.0Ah (Li-ion) | Charging time (usable / full) | 65 / 80min. | Drill & Driver | EY 79A2 X | Impact Driver | EY 75A7 X | Battery | 2 x EY 9L54 B | Charger | EY 0L82 B | | |
| Voltage | 18V | | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 5.0Ah (Li-ion) | | | | | | | | | | | | | | | | | | |
| Charging time (usable / full) | 65 / 80min. | | | | | | | | | | | | | | | | | | |
| Drill & Driver | EY 79A2 X | | | | | | | | | | | | | | | | | | |
| Impact Driver | EY 75A7 X | | | | | | | | | | | | | | | | | | |
| Battery | 2 x EY 9L54 B | | | | | | | | | | | | | | | | | | |
| Charger | EY 0L82 B | | | | | | | | | | | | | | | | | | |

TWO PIECE SETS

| VOLTAGE (V) / CAPACITY (AH) | MODEL / FEATURES | | | | | | | | | | | | | | | | |
|---|---|---------|-----------|--|-------------------|-------------------------------|--------------|----------------|-----------|---------------|-----------|------------|---------------|---------|---------------|---------|-----------|
| <p>NEW 18V 3.0Ah</p>  <p>EYC 217 PN2G</p> <p>Two Piece Set</p> <ul style="list-style-type: none"> ■ Drill Driver EY 79A2 X ■ Impact Driver EY 75A7 X ■ 2 x battery EY 9L53 B with 3.0Ah ■ 1 x charger EY 0L82 B | <table border="1"> <tr><td>Voltage</td><td>18V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>3.0Ah (Li-ion)</td></tr> <tr><td>Charging time (usable / full)</td><td>45 / 60min.</td></tr> <tr><td>Drill & Driver</td><td>EY 79A2 X</td></tr> <tr><td>Impact Driver</td><td>EY 75A7 X</td></tr> <tr><td>Battery</td><td>2 x EY 9L53 B</td></tr> <tr><td>Charger</td><td>EY 0L82 B</td></tr> </table> | Voltage | 18V | Battery capacity accord. to IEC (technology) | 3.0Ah (Li-ion) | Charging time (usable / full) | 45 / 60min. | Drill & Driver | EY 79A2 X | Impact Driver | EY 75A7 X | Battery | 2 x EY 9L53 B | Charger | EY 0L82 B | | |
| Voltage | 18V | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 3.0Ah (Li-ion) | | | | | | | | | | | | | | | | |
| Charging time (usable / full) | 45 / 60min. | | | | | | | | | | | | | | | | |
| Drill & Driver | EY 79A2 X | | | | | | | | | | | | | | | | |
| Impact Driver | EY 75A7 X | | | | | | | | | | | | | | | | |
| Battery | 2 x EY 9L53 B | | | | | | | | | | | | | | | | |
| Charger | EY 0L82 B | | | | | | | | | | | | | | | | |
| <p>NEW 14.4V 4.2Ah</p>  <p>EYC 217 LS2F</p> <p>Two Piece Set</p> <ul style="list-style-type: none"> ■ Drill Driver EY 79A2 X ■ Impact Driver EY 75A7 X ■ 2 x battery EY 9L45 B with 4.2Ah ■ 1 x charger EY 0L82 B | <table border="1"> <tr><td>Voltage</td><td>14.4V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>4.2Ah (Li-ion)</td></tr> <tr><td>Charging time (usable / full)</td><td>50 / 60min.</td></tr> <tr><td>Drill & Driver</td><td>EY 79A2 X</td></tr> <tr><td>Impact Driver</td><td>EY 75A7 X</td></tr> <tr><td>Battery</td><td>2 x EY 9L45 B</td></tr> <tr><td>Charger</td><td>EY 0L82 B</td></tr> </table> | Voltage | 14.4V | Battery capacity accord. to IEC (technology) | 4.2Ah (Li-ion) | Charging time (usable / full) | 50 / 60min. | Drill & Driver | EY 79A2 X | Impact Driver | EY 75A7 X | Battery | 2 x EY 9L45 B | Charger | EY 0L82 B | | |
| Voltage | 14.4V | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 4.2Ah (Li-ion) | | | | | | | | | | | | | | | | |
| Charging time (usable / full) | 50 / 60min. | | | | | | | | | | | | | | | | |
| Drill & Driver | EY 79A2 X | | | | | | | | | | | | | | | | |
| Impact Driver | EY 75A7 X | | | | | | | | | | | | | | | | |
| Battery | 2 x EY 9L45 B | | | | | | | | | | | | | | | | |
| Charger | EY 0L82 B | | | | | | | | | | | | | | | | |
| <p>NEW 18V 5.0Ah</p>  <p>EYC 218 LJ2G</p> <p>Two Piece Set</p> <ul style="list-style-type: none"> ■ Drill Driver EY 7950 X ■ Impact Driver EY 75A7 X ■ 2 x battery EY 9L54 B with 5.0Ah ■ 1 x charger EY 0L82 B | <table border="1"> <tr><td>Voltage</td><td>18V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>5.0Ah (Li-ion)</td></tr> <tr><td>Charging time (usable / full)</td><td>65 / 80min.</td></tr> <tr><td>Drill & Driver</td><td>EY 7950 X</td></tr> <tr><td>Impact Driver</td><td>EY 75A7 X</td></tr> <tr><td>Battery</td><td>2 x EY 9L54 B</td></tr> <tr><td>Charger</td><td>EY 0L82 B</td></tr> </table> | Voltage | 18V | Battery capacity accord. to IEC (technology) | 5.0Ah (Li-ion) | Charging time (usable / full) | 65 / 80min. | Drill & Driver | EY 7950 X | Impact Driver | EY 75A7 X | Battery | 2 x EY 9L54 B | Charger | EY 0L82 B | | |
| Voltage | 18V | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 5.0Ah (Li-ion) | | | | | | | | | | | | | | | | |
| Charging time (usable / full) | 65 / 80min. | | | | | | | | | | | | | | | | |
| Drill & Driver | EY 7950 X | | | | | | | | | | | | | | | | |
| Impact Driver | EY 75A7 X | | | | | | | | | | | | | | | | |
| Battery | 2 x EY 9L54 B | | | | | | | | | | | | | | | | |
| Charger | EY 0L82 B | | | | | | | | | | | | | | | | |
| <p>10.8V 1.5Ah</p>  <p>EYC 110 LA2L</p> <p>Combo-Set</p> <ul style="list-style-type: none"> ■ Drill & Driver EY 7430 ■ Impact Driver EY 7530 ■ Flashlight EY 3732 B ■ 2 x battery EY 9L32 B with 1.5Ah ■ 1 x charger EY 0L32 B | <table border="1"> <tr><td>Voltage</td><td>10,8 Volt</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>1,5 Ah (Li-Ionen)</td></tr> <tr><td>Charging time (usable / full)</td><td>40 / 50 Min.</td></tr> <tr><td>Drill & Driver</td><td>EY 7430</td></tr> <tr><td>Impact Driver</td><td>EY 7530</td></tr> <tr><td>Flashlight</td><td>EY 3732 B</td></tr> <tr><td>Battery</td><td>2 x EY 9L32 B</td></tr> <tr><td>Charger</td><td>EY 0L32 B</td></tr> </table> | Voltage | 10,8 Volt | Battery capacity accord. to IEC (technology) | 1,5 Ah (Li-Ionen) | Charging time (usable / full) | 40 / 50 Min. | Drill & Driver | EY 7430 | Impact Driver | EY 7530 | Flashlight | EY 3732 B | Battery | 2 x EY 9L32 B | Charger | EY 0L32 B |
| Voltage | 10,8 Volt | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 1,5 Ah (Li-Ionen) | | | | | | | | | | | | | | | | |
| Charging time (usable / full) | 40 / 50 Min. | | | | | | | | | | | | | | | | |
| Drill & Driver | EY 7430 | | | | | | | | | | | | | | | | |
| Impact Driver | EY 7530 | | | | | | | | | | | | | | | | |
| Flashlight | EY 3732 B | | | | | | | | | | | | | | | | |
| Battery | 2 x EY 9L32 B | | | | | | | | | | | | | | | | |
| Charger | EY 0L32 B | | | | | | | | | | | | | | | | |

HAMMER DRILL & DRIVER

| VOLTAGE (V) / CAPACITY (AH) | MODEL / FEATURES | | | | | | | | | | | | | | | | |
|---|---|---------|-------|--|----------------|--|-------------|---------|---------------|------------------------|-------|--|---------------------|---|-----------|--|--------------------------|
| <p>21.6V 4.2Ah</p>  <p>EY 7960 LS2S (BLACK EDITION)</p> <ul style="list-style-type: none"> ■ High-performance 4.2Ah Li-ion battery pack ■ Light weight 2.5kg (incl. battery) ■ 13mm high-capacity drill chuck (keyless) ■ Powerful percussion mechanism for fast drilling ■ 18-stage clutch plus drill position ■ Reversible ■ Secure front handle ■ Incl. second battery pack | <table border="1"> <tr><td>Voltage</td><td>21.6V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>4.2Ah (Li-ion)</td></tr> <tr><td>Charging time (usable / full)</td><td>65 / 85min.</td></tr> <tr><td>Battery</td><td>2 x EY 9L62 B</td></tr> <tr><td>Weight (incl. battery)</td><td>2.5kg</td></tr> <tr><td>Speed at no load (low / high) in min⁻¹ (rpm)</td><td>100-400 / 350-1,500</td></tr> <tr><td>Max. torque (stalling / instant torque)</td><td>42 / 63Nm</td></tr> <tr><td>Percussion mechanism (blows per minute)</td><td>7,200 - 27,000</td></tr> </table> | Voltage | 21.6V | Battery capacity accord. to IEC (technology) | 4.2Ah (Li-ion) | Charging time (usable / full) | 65 / 85min. | Battery | 2 x EY 9L62 B | Weight (incl. battery) | 2.5kg | Speed at no load (low / high) in min ⁻¹ (rpm) | 100-400 / 350-1,500 | Max. torque (stalling / instant torque) | 42 / 63Nm | Percussion mechanism (blows per minute) | 7,200 - 27,000 |
| Voltage | 21.6V | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 4.2Ah (Li-ion) | | | | | | | | | | | | | | | | |
| Charging time (usable / full) | 65 / 85min. | | | | | | | | | | | | | | | | |
| Battery | 2 x EY 9L62 B | | | | | | | | | | | | | | | | |
| Weight (incl. battery) | 2.5kg | | | | | | | | | | | | | | | | |
| Speed at no load (low / high) in min ⁻¹ (rpm) | 100-400 / 350-1,500 | | | | | | | | | | | | | | | | |
| Max. torque (stalling / instant torque) | 42 / 63Nm | | | | | | | | | | | | | | | | |
| Percussion mechanism (blows per minute) | 7,200 - 27,000 | | | | | | | | | | | | | | | | |
| <p>NEW 18V 5.0Ah</p>  <p>EY 79A2 LJ2G</p> <ul style="list-style-type: none"> ■ High-performance 5.0Ah Li-ion battery pack ■ New design high power and durable Brushless motor ■ New 'Speed control function' ■ Fresh new 'Carbon' design ■ Electronic speed control ■ Battery capacity indicator, belt hook and LED light ■ Durable design with compact body 188mm ■ Incl. second battery pack | <table border="1"> <tr><td>Voltage</td><td>18V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>5.0Ah (Li-ion)</td></tr> <tr><td>Charging time with EY 0L82 B (usable / full)</td><td>65 / 80min.</td></tr> <tr><td>Battery</td><td>2 x EY 9L54 B</td></tr> <tr><td>Weight (incl. battery)</td><td>2.1kg</td></tr> <tr><td>Speed at no load (low / high) in min⁻¹ (rpm)</td><td>30-470 / 70-1,580</td></tr> <tr><td>Max. torque (stalling / instant torque)</td><td>32 / 50Nm</td></tr> <tr><td>Percussion mechanism (low / high) blows per minute</td><td>540-8,500 / 1,260-28,400</td></tr> </table> | Voltage | 18V | Battery capacity accord. to IEC (technology) | 5.0Ah (Li-ion) | Charging time with EY 0L82 B (usable / full) | 65 / 80min. | Battery | 2 x EY 9L54 B | Weight (incl. battery) | 2.1kg | Speed at no load (low / high) in min ⁻¹ (rpm) | 30-470 / 70-1,580 | Max. torque (stalling / instant torque) | 32 / 50Nm | Percussion mechanism (low / high) blows per minute | 540-8,500 / 1,260-28,400 |
| Voltage | 18V | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 5.0Ah (Li-ion) | | | | | | | | | | | | | | | | |
| Charging time with EY 0L82 B (usable / full) | 65 / 80min. | | | | | | | | | | | | | | | | |
| Battery | 2 x EY 9L54 B | | | | | | | | | | | | | | | | |
| Weight (incl. battery) | 2.1kg | | | | | | | | | | | | | | | | |
| Speed at no load (low / high) in min ⁻¹ (rpm) | 30-470 / 70-1,580 | | | | | | | | | | | | | | | | |
| Max. torque (stalling / instant torque) | 32 / 50Nm | | | | | | | | | | | | | | | | |
| Percussion mechanism (low / high) blows per minute | 540-8,500 / 1,260-28,400 | | | | | | | | | | | | | | | | |

HAMMER DRILL & DRIVER

| VOLTAGE (V) / CAPACITY (AH) | MODEL / FEATURES | | | | | | | | | | | | | | | | | |
|---|---|---|---------|------------|--|----------------------|---|-------------|----------------------------------|---------------|---|--------------------|--|--------------------|---|--------------------------|--|--------------------------|
| <p>NEW</p> <p>18V 3.0Ah</p>  <p>BRUSHLESS MOTOR</p> <p>14.4V / 18V</p> <p>TOUGH TOOL IP</p> | <p>EY 79A2 PN2G</p> <ul style="list-style-type: none"> High-performance 3.0Ah Li-ion battery pack New design high power and durable Brushless motor New 'Speed control function' New 'Carbon' design Electronic speed control Battery capacity indicator, belt hook and LED light Durable design with compact body 188mm Incl. second battery pack | <table border="1"> <tr><td>Voltage</td><td>18V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>3.0Ah (Li-ion)</td></tr> <tr><td>Charging time with EY 0L82 B (usable / full)</td><td>45 / 60min.</td></tr> <tr><td>Battery</td><td>2 x EY 9L53 B</td></tr> <tr><td>Weight (incl. battery)</td><td>1.85kg</td></tr> <tr><td>Speed at no load (low / high) in min⁻¹ (rpm)</td><td>30-470 / 70-1,580</td></tr> <tr><td>Max. torque (stalling / instant torque)</td><td>32 / 50Nm</td></tr> <tr><td>Percussion mechanism (low / high) blows per minute</td><td>540-8,500 / 1,260-28,400</td></tr> </table> | Voltage | 18V | Battery capacity accord. to IEC (technology) | 3.0Ah (Li-ion) | Charging time with EY 0L82 B (usable / full) | 45 / 60min. | Battery | 2 x EY 9L53 B | Weight (incl. battery) | 1.85kg | Speed at no load (low / high) in min ⁻¹ (rpm) | 30-470 / 70-1,580 | Max. torque (stalling / instant torque) | 32 / 50Nm | Percussion mechanism (low / high) blows per minute | 540-8,500 / 1,260-28,400 |
| Voltage | 18V | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 3.0Ah (Li-ion) | | | | | | | | | | | | | | | | | |
| Charging time with EY 0L82 B (usable / full) | 45 / 60min. | | | | | | | | | | | | | | | | | |
| Battery | 2 x EY 9L53 B | | | | | | | | | | | | | | | | | |
| Weight (incl. battery) | 1.85kg | | | | | | | | | | | | | | | | | |
| Speed at no load (low / high) in min ⁻¹ (rpm) | 30-470 / 70-1,580 | | | | | | | | | | | | | | | | | |
| Max. torque (stalling / instant torque) | 32 / 50Nm | | | | | | | | | | | | | | | | | |
| Percussion mechanism (low / high) blows per minute | 540-8,500 / 1,260-28,400 | | | | | | | | | | | | | | | | | |
| <p>NEW</p> <p>18V 14.4V</p>  <p>BRUSHLESS MOTOR</p> <p>14.4V / 18V</p> <p>TOUGH TOOL IP</p> | <p>EY 79A2 X</p> <ul style="list-style-type: none"> Such as EY 79A2 LJ2G / PN2G Without battery and charger Compatible with the following batteries <p>18V: EY 9L54 B, EY 9L53 B, EY 9L52 B, EY 9L51 B, EY 9L50 B 14.4V: EY 9L47 B, EY 9L45 B, EY 9L44 B, EY 9L42 B</p> | <table border="1"> <tr><td>Voltage</td><td>18 / 14.4V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>Depending on battery</td></tr> <tr><td>Charging time with EY 0L82 B, EY 9L54 B (usable / full)</td><td>65 / 80min.</td></tr> <tr><td>Weight (incl. Battery EY 9L54 B)</td><td>2.1kg</td></tr> <tr><td>Speed at no load with EY 9L54 B in rpm (low / high)</td><td>30-470 / 70-1,580</td></tr> <tr><td>Max. torque with EY 9L54 B (stalling / instant torque)</td><td>32 / 50Nm</td></tr> <tr><td>Percussion mechanism with EY 9L54 B (low / high) blows per minute</td><td>540-8,500 / 1,260-28,400</td></tr> </table> | Voltage | 18 / 14.4V | Battery capacity accord. to IEC (technology) | Depending on battery | Charging time with EY 0L82 B, EY 9L54 B (usable / full) | 65 / 80min. | Weight (incl. Battery EY 9L54 B) | 2.1kg | Speed at no load with EY 9L54 B in rpm (low / high) | 30-470 / 70-1,580 | Max. torque with EY 9L54 B (stalling / instant torque) | 32 / 50Nm | Percussion mechanism with EY 9L54 B (low / high) blows per minute | 540-8,500 / 1,260-28,400 | | |
| Voltage | 18 / 14.4V | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | Depending on battery | | | | | | | | | | | | | | | | | |
| Charging time with EY 0L82 B, EY 9L54 B (usable / full) | 65 / 80min. | | | | | | | | | | | | | | | | | |
| Weight (incl. Battery EY 9L54 B) | 2.1kg | | | | | | | | | | | | | | | | | |
| Speed at no load with EY 9L54 B in rpm (low / high) | 30-470 / 70-1,580 | | | | | | | | | | | | | | | | | |
| Max. torque with EY 9L54 B (stalling / instant torque) | 32 / 50Nm | | | | | | | | | | | | | | | | | |
| Percussion mechanism with EY 9L54 B (low / high) blows per minute | 540-8,500 / 1,260-28,400 | | | | | | | | | | | | | | | | | |
| <p>NEW</p> <p>18V 5.0Ah</p>  <p>TOUGH TOOL IP</p> | <p>EY 7950 LJ2S (BLACK EDITION)</p> <ul style="list-style-type: none"> High-performance 5.0Ah Li-ion battery pack Light weight 2.3kg (incl. battery) 18-stage clutch plus drill position 13mm high-capacity drill chuck (keyless) Electric speed control Electric brake; reversible Secure front handle Incl. second battery pack | <table border="1"> <tr><td>Voltage</td><td>18V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>5.0Ah (Li-ion)</td></tr> <tr><td>Charging time (usable / full)</td><td>65 / 80min.</td></tr> <tr><td>Battery</td><td>2 x EY 9L54 B</td></tr> <tr><td>Weight (incl. battery)</td><td>2.3kg</td></tr> <tr><td>Speed at no load (low / high) in min⁻¹ (rpm)</td><td>50-430 / 160-1.650</td></tr> <tr><td>Max. torque (stalling / instant torque)</td><td>40 / 57Nm</td></tr> <tr><td>Percussion mechanism (blows per minute)</td><td>7,740 - 29,700</td></tr> </table> | Voltage | 18V | Battery capacity accord. to IEC (technology) | 5.0Ah (Li-ion) | Charging time (usable / full) | 65 / 80min. | Battery | 2 x EY 9L54 B | Weight (incl. battery) | 2.3kg | Speed at no load (low / high) in min ⁻¹ (rpm) | 50-430 / 160-1.650 | Max. torque (stalling / instant torque) | 40 / 57Nm | Percussion mechanism (blows per minute) | 7,740 - 29,700 |
| Voltage | 18V | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 5.0Ah (Li-ion) | | | | | | | | | | | | | | | | | |
| Charging time (usable / full) | 65 / 80min. | | | | | | | | | | | | | | | | | |
| Battery | 2 x EY 9L54 B | | | | | | | | | | | | | | | | | |
| Weight (incl. battery) | 2.3kg | | | | | | | | | | | | | | | | | |
| Speed at no load (low / high) in min ⁻¹ (rpm) | 50-430 / 160-1.650 | | | | | | | | | | | | | | | | | |
| Max. torque (stalling / instant torque) | 40 / 57Nm | | | | | | | | | | | | | | | | | |
| Percussion mechanism (blows per minute) | 7,740 - 29,700 | | | | | | | | | | | | | | | | | |
| <p>18V</p>  <p>TOUGH TOOL IP</p> | <p>EY 7950 X (BLACK EDITION)</p> <ul style="list-style-type: none"> Such as EY 7950 LJ2S Without battery and charger Compatible with the following batteries <p>18V: EY 9L54 B, EY 9L53 B, EY 9L52 B, EY 9L51 B, EY 9L50 B</p> | <table border="1"> <tr><td>Voltage</td><td>18V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>Depending on battery</td></tr> <tr><td>Charging time with EY 9L54 B (usable / full)</td><td>65 / 80min.</td></tr> <tr><td>Weight (incl. Battery EY 9L54 B)</td><td>2.3kg</td></tr> <tr><td>Speed at no load with EY 9L54 B (low / high) in min⁻¹ (rpm)</td><td>50-430 / 160-1.650</td></tr> <tr><td>Max. torque with EY 9L54 B (stalling / instant torque)</td><td>40 / 57Nm</td></tr> <tr><td>Percussion mechanism EY 9L54 B (blows per minute)</td><td>7,740 - 29,700</td></tr> </table> | Voltage | 18V | Battery capacity accord. to IEC (technology) | Depending on battery | Charging time with EY 9L54 B (usable / full) | 65 / 80min. | Weight (incl. Battery EY 9L54 B) | 2.3kg | Speed at no load with EY 9L54 B (low / high) in min ⁻¹ (rpm) | 50-430 / 160-1.650 | Max. torque with EY 9L54 B (stalling / instant torque) | 40 / 57Nm | Percussion mechanism EY 9L54 B (blows per minute) | 7,740 - 29,700 | | |
| Voltage | 18V | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | Depending on battery | | | | | | | | | | | | | | | | | |
| Charging time with EY 9L54 B (usable / full) | 65 / 80min. | | | | | | | | | | | | | | | | | |
| Weight (incl. Battery EY 9L54 B) | 2.3kg | | | | | | | | | | | | | | | | | |
| Speed at no load with EY 9L54 B (low / high) in min ⁻¹ (rpm) | 50-430 / 160-1.650 | | | | | | | | | | | | | | | | | |
| Max. torque with EY 9L54 B (stalling / instant torque) | 40 / 57Nm | | | | | | | | | | | | | | | | | |
| Percussion mechanism EY 9L54 B (blows per minute) | 7,740 - 29,700 | | | | | | | | | | | | | | | | | |
| <p>14.4V 4.2Ah</p>  <p>TOUGH TOOL IP</p> | <p>EY 7940 LS2S</p> <ul style="list-style-type: none"> High-performance 4.2Ah Li-ion battery pack Light weight 1.8kg (incl. battery) 18-stage clutch plus drill position 13mm high-capacity drill chuck (keyless) Powerful percussion mechanism for fast drilling Electric speed control, electric brake; reversible Secure front handle Incl. second battery pack | <table border="1"> <tr><td>Voltage</td><td>14.4V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>4.2Ah (Li-ion)</td></tr> <tr><td>Charging time (usable / full)</td><td>50 / 60min.</td></tr> <tr><td>Battery</td><td>2 x EY 9L45 B</td></tr> <tr><td>Weight (incl. battery)</td><td>1.8kg</td></tr> <tr><td>Speed at no load (low / high) in min⁻¹ (rpm)</td><td>70-400 / 200-1,400</td></tr> <tr><td>Max. torque (stalling / instant torque)</td><td>28 / 41.5Nm</td></tr> <tr><td>Percussion mechanism (blows per minute)</td><td>7,200 - 25,200</td></tr> </table> | Voltage | 14.4V | Battery capacity accord. to IEC (technology) | 4.2Ah (Li-ion) | Charging time (usable / full) | 50 / 60min. | Battery | 2 x EY 9L45 B | Weight (incl. battery) | 1.8kg | Speed at no load (low / high) in min ⁻¹ (rpm) | 70-400 / 200-1,400 | Max. torque (stalling / instant torque) | 28 / 41.5Nm | Percussion mechanism (blows per minute) | 7,200 - 25,200 |
| Voltage | 14.4V | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 4.2Ah (Li-ion) | | | | | | | | | | | | | | | | | |
| Charging time (usable / full) | 50 / 60min. | | | | | | | | | | | | | | | | | |
| Battery | 2 x EY 9L45 B | | | | | | | | | | | | | | | | | |
| Weight (incl. battery) | 1.8kg | | | | | | | | | | | | | | | | | |
| Speed at no load (low / high) in min ⁻¹ (rpm) | 70-400 / 200-1,400 | | | | | | | | | | | | | | | | | |
| Max. torque (stalling / instant torque) | 28 / 41.5Nm | | | | | | | | | | | | | | | | | |
| Percussion mechanism (blows per minute) | 7,200 - 25,200 | | | | | | | | | | | | | | | | | |
| <p>14.4V</p>  <p>TOUGH TOOL IP</p> | <p>EY 7940 X</p> <ul style="list-style-type: none"> Such as EY 7940 LS2S Without battery and charger Compatible with the following batteries <p>14.4V: EY 9L47 B, EY 9L45 B, EY 9L44 B, EY 9L42 B</p> | <table border="1"> <tr><td>Voltage</td><td>14.4V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>Depending on battery</td></tr> <tr><td>Charging time with EY 9L45 B (usable / full)</td><td>50 / 60min.</td></tr> <tr><td>Weight (incl. Battery EY 9L45 B)</td><td>1.8kg</td></tr> <tr><td>Speed at no load with EY 9L45 B (low / high) in min⁻¹ (rpm)</td><td>70-400 / 200-1,400</td></tr> <tr><td>Max. torque with EY 9L45 B (stalling / instant torque)</td><td>28 / 41.5Nm</td></tr> <tr><td>Percussion mechanism EY 9L45 B (blows per minute)</td><td>7,200 - 25,200</td></tr> </table> | Voltage | 14.4V | Battery capacity accord. to IEC (technology) | Depending on battery | Charging time with EY 9L45 B (usable / full) | 50 / 60min. | Weight (incl. Battery EY 9L45 B) | 1.8kg | Speed at no load with EY 9L45 B (low / high) in min ⁻¹ (rpm) | 70-400 / 200-1,400 | Max. torque with EY 9L45 B (stalling / instant torque) | 28 / 41.5Nm | Percussion mechanism EY 9L45 B (blows per minute) | 7,200 - 25,200 | | |
| Voltage | 14.4V | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | Depending on battery | | | | | | | | | | | | | | | | | |
| Charging time with EY 9L45 B (usable / full) | 50 / 60min. | | | | | | | | | | | | | | | | | |
| Weight (incl. Battery EY 9L45 B) | 1.8kg | | | | | | | | | | | | | | | | | |
| Speed at no load with EY 9L45 B (low / high) in min ⁻¹ (rpm) | 70-400 / 200-1,400 | | | | | | | | | | | | | | | | | |
| Max. torque with EY 9L45 B (stalling / instant torque) | 28 / 41.5Nm | | | | | | | | | | | | | | | | | |
| Percussion mechanism EY 9L45 B (blows per minute) | 7,200 - 25,200 | | | | | | | | | | | | | | | | | |

HAMMER DRILL & DRIVER – BATTERY CAPACITIES

| VOLTAGE | | 21.6V | 14.4V | |
|--|--|--|---------------|-------|
| MODEL | | EY 7960 LS2S | EY 7940 LS2S | |
| BATTERY | | EY 9L62 B(LS) | EY 9L45 B(LS) | |
| Screwing | Wood screws in yellow pine* | ∅ 4.1mm x 25mm | 1.700 | 1.200 |
| | Wood screws in yellow pine* | ∅ 6mm x 80mm | - | - |
| | Wood screws in yellow pine** | ∅ 8mm x 80mm | 570 | - |
| | Self-drilling screws in SPC* | ∅ 4mm x 13mm t=1.6mm | 1.200 | 750 |
| | No plug screws in mortar* | ∅ 6mm x 45mm | 1.200 | 1.200 |
| Drilling | Holes in plaster board + Plywood / wooding core* | Plaster board 12.5mm + Plywood 12mm ∅ 68mm x 24.5mm | 190 | - |
| | Holes in plaster board + Plywood** | Plaster board 12.5mm + Plywood 12mm ∅ 125mm x 24.5mm | 45 | - |
| | Holes in mortar* | ∅ 6.5mm x 30mm | - | 110 |
| | Holes in mortar* | ∅ 10mm x 30mm | 120 | 85 |
| | Holes in masonry* | ∅ 5mm x 40mm depth | 140 | 180 |
| | Holes in SPC / hole saw* | ∅ 21mm t=1.6mm | 65 | 25 |
| | Holes in SPC / hole saw** | ∅ 33mm t=1.6mm | 65 | 20 |
| | Holes in yellow pine* | ∅ 18mm x 120mm | 150 | 95 |
| Holes in yellow pine (EY 7960*, EY 7950*, EY 7940**) | ∅ 30mm x 40mm | 210 | 150 | |

| VOLTAGE | | 18V | 18V | |
|------------------------|--|----------------------|---------------|---------------|
| MODEL | | EY 79A2 LJ2G | EY 79A2 PN2G | |
| BATTERY | | EY 9L54 B(LJ) | EY 9L53 B(PN) | |
| Screwing | Wood screws in yellow pine* | ∅ 4.1mm x 25mm | Approx. 1,750 | Approx. 1,050 |
| | Self-drilling screws in SPC / Metal sheet* | ∅ 4mm x 13mm t=1.6mm | Approx. 1,250 | Approx. 740 |
| | Screwing in mortar** | ∅ 6mm x 45mm | Approx. 790 | Approx. 470 |
| Drilling | Holes in mortar* | ∅ 6.5mm x 30mm depth | Approx. 220 | Approx. 130 |
| | Holes in mortar* | ∅ 10mm x 30mm depth | Approx. 160 | Approx. 100 |
| | Holes in masonry* | ∅ 5mm x 40mm | Approx. 260 | Approx. 150 |
| | Holes in sheet metal* | ∅ 21mm t=1.6mm | Approx. 50 | Approx. 30 |
| | Holes in sheet metal** | ∅ 33mm t=1.6mm | Approx. 75 | Approx. 45 |
| | Holes in yellow pine* | ∅ 18mm x 120mm | Approx. 140 | Approx. 80 |
| Holes in yellow pine** | ∅ 30mm x 40mm | Approx. 280 | Approx. 170 | |

Depending on test condition, the measurement result is sometimes different to that of operation manual. The table shows average values of working capacity per fully charged battery.
 * High mode ** Low mode

SDS-PLUS ROTARY HAMMER

| VOLTAGE (V) / CAPACITY (AH) | MODEL / FEATURES | | | | | | | | | | | | | | | | | |
|--|---|---|---------|------------|--|----------------------|--|-------------|----------------------------------|---------------|--|-----------|--|-----------------------|-------------------------------------|-----------------------|-------------|---------------|
| 28.8V 3.0Ah | EY 7880 LP2C (BLACK EDITION) <ul style="list-style-type: none"> High-performance 3.0Ah Li-ion battery pack Light weight 3.85kg (incl. Battery) Hard and soft hammering mode for best results in different materials Slow and high speed drilling mode for different materials Chisel attachment as standard accessories Electric speed control and electric brake Vibration-damping soft rubber grip Incl. second battery pack | <table border="1"> <tr><td>Voltage</td><td>28.8V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>3.0Ah (Li-ion)</td></tr> <tr><td>Charging time (usable / full)</td><td>60 / 80min.</td></tr> <tr><td>Battery</td><td>2 x EY 9L82 B</td></tr> <tr><td>Weight (incl. battery)</td><td>3.85kg</td></tr> <tr><td>Speed at no load in min⁻¹ (rpm)</td><td>0 - 920</td></tr> <tr><td>Blows per minute (soft / hard mode)</td><td>0 - 2,800 / 0 - 4,500</td></tr> <tr><td>Drill chuck</td><td>SDS-plus type</td></tr> </table> | Voltage | 28.8V | Battery capacity accord. to IEC (technology) | 3.0Ah (Li-ion) | Charging time (usable / full) | 60 / 80min. | Battery | 2 x EY 9L82 B | Weight (incl. battery) | 3.85kg | Speed at no load in min ⁻¹ (rpm) | 0 - 920 | Blows per minute (soft / hard mode) | 0 - 2,800 / 0 - 4,500 | Drill chuck | SDS-plus type |
| Voltage | 28.8V | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 3.0Ah (Li-ion) | | | | | | | | | | | | | | | | | |
| Charging time (usable / full) | 60 / 80min. | | | | | | | | | | | | | | | | | |
| Battery | 2 x EY 9L82 B | | | | | | | | | | | | | | | | | |
| Weight (incl. battery) | 3.85kg | | | | | | | | | | | | | | | | | |
| Speed at no load in min ⁻¹ (rpm) | 0 - 920 | | | | | | | | | | | | | | | | | |
| Blows per minute (soft / hard mode) | 0 - 2,800 / 0 - 4,500 | | | | | | | | | | | | | | | | | |
| Drill chuck | SDS-plus type | | | | | | | | | | | | | | | | | |
| 28.8V | EY 7880 X (BLACK EDITION) <ul style="list-style-type: none"> Such as EY 7880 LP2C Without battery and charger Compatible with the following batteries EY 9L82 B and EY 9L81 B | <table border="1"> <tr><td>Voltage</td><td>28.8V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>Depending on battery</td></tr> <tr><td>Charging time (usable / full)</td><td>60 / 80min.</td></tr> <tr><td>Weight (incl. battery)</td><td>3.85kg</td></tr> <tr><td>Speed at no load in min⁻¹ (rpm)</td><td>0 - 920</td></tr> <tr><td>Blows per minute (soft / hard mode)</td><td>0 - 2,800 / 0 - 4,500</td></tr> <tr><td>Drill chuck</td><td>SDS-plus type</td></tr> </table> | Voltage | 28.8V | Battery capacity accord. to IEC (technology) | Depending on battery | Charging time (usable / full) | 60 / 80min. | Weight (incl. battery) | 3.85kg | Speed at no load in min ⁻¹ (rpm) | 0 - 920 | Blows per minute (soft / hard mode) | 0 - 2,800 / 0 - 4,500 | Drill chuck | SDS-plus type | | |
| Voltage | 28.8V | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | Depending on battery | | | | | | | | | | | | | | | | | |
| Charging time (usable / full) | 60 / 80min. | | | | | | | | | | | | | | | | | |
| Weight (incl. battery) | 3.85kg | | | | | | | | | | | | | | | | | |
| Speed at no load in min ⁻¹ (rpm) | 0 - 920 | | | | | | | | | | | | | | | | | |
| Blows per minute (soft / hard mode) | 0 - 2,800 / 0 - 4,500 | | | | | | | | | | | | | | | | | |
| Drill chuck | SDS-plus type | | | | | | | | | | | | | | | | | |
| NEW 18V 5.0Ah | EY 78A1 LJ2G (BLACK EDITION) <ul style="list-style-type: none"> High-performance 5.0Ah Li-ion battery pack Light weight 2.6kg (incl. battery) Dual function: Rotary Hammer or Drill & Driver 5 stage torque clutch plus drill position Drill chuck SDS-plus 'T shape' design for improved balance and ergonomics Reversible Incl. second battery pack | <table border="1"> <tr><td>Voltage</td><td>18V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>5.0Ah (Li-ion)</td></tr> <tr><td>Charging time (usable / full)</td><td>65 / 80min.</td></tr> <tr><td>Battery</td><td>2 x EY 9L54 B</td></tr> <tr><td>Weight (incl. battery)</td><td>2.6kg</td></tr> <tr><td>Speed at no load in min⁻¹ (rpm)</td><td>0 - 1,250</td></tr> <tr><td>Blows per minute (soft / hard mode)</td><td>0 - 4,750</td></tr> <tr><td>Drill chuck</td><td>SDS-plus type</td></tr> </table> | Voltage | 18V | Battery capacity accord. to IEC (technology) | 5.0Ah (Li-ion) | Charging time (usable / full) | 65 / 80min. | Battery | 2 x EY 9L54 B | Weight (incl. battery) | 2.6kg | Speed at no load in min ⁻¹ (rpm) | 0 - 1,250 | Blows per minute (soft / hard mode) | 0 - 4,750 | Drill chuck | SDS-plus type |
| Voltage | 18V | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 5.0Ah (Li-ion) | | | | | | | | | | | | | | | | | |
| Charging time (usable / full) | 65 / 80min. | | | | | | | | | | | | | | | | | |
| Battery | 2 x EY 9L54 B | | | | | | | | | | | | | | | | | |
| Weight (incl. battery) | 2.6kg | | | | | | | | | | | | | | | | | |
| Speed at no load in min ⁻¹ (rpm) | 0 - 1,250 | | | | | | | | | | | | | | | | | |
| Blows per minute (soft / hard mode) | 0 - 4,750 | | | | | | | | | | | | | | | | | |
| Drill chuck | SDS-plus type | | | | | | | | | | | | | | | | | |
| NEW 18V 3.0Ah | EY 78A1 PN2G (BLACK EDITION) <ul style="list-style-type: none"> High-performance 3.0Ah Li-ion battery pack Light weight 2.45kg (incl. battery) Dual function: Rotary Hammer or Drill & Driver 5 stage torque clutch plus drill position Drill chuck SDS-plus 'T shape' design for improved balance and ergonomics Reversible Incl. second battery pack | <table border="1"> <tr><td>Voltage</td><td>18V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>3.0Ah (Li-ion)</td></tr> <tr><td>Charging time (usable / full)</td><td>45 / 60min.</td></tr> <tr><td>Battery</td><td>2 x EY 9L53 B</td></tr> <tr><td>Weight (incl. battery)</td><td>2.45kg</td></tr> <tr><td>Speed at no load in min⁻¹ (rpm)</td><td>0 - 1,000</td></tr> <tr><td>Blows per minute (soft / hard mode)</td><td>0 - 3,800</td></tr> <tr><td>Drill chuck</td><td>SDS-plus type</td></tr> </table> | Voltage | 18V | Battery capacity accord. to IEC (technology) | 3.0Ah (Li-ion) | Charging time (usable / full) | 45 / 60min. | Battery | 2 x EY 9L53 B | Weight (incl. battery) | 2.45kg | Speed at no load in min ⁻¹ (rpm) | 0 - 1,000 | Blows per minute (soft / hard mode) | 0 - 3,800 | Drill chuck | SDS-plus type |
| Voltage | 18V | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 3.0Ah (Li-ion) | | | | | | | | | | | | | | | | | |
| Charging time (usable / full) | 45 / 60min. | | | | | | | | | | | | | | | | | |
| Battery | 2 x EY 9L53 B | | | | | | | | | | | | | | | | | |
| Weight (incl. battery) | 2.45kg | | | | | | | | | | | | | | | | | |
| Speed at no load in min ⁻¹ (rpm) | 0 - 1,000 | | | | | | | | | | | | | | | | | |
| Blows per minute (soft / hard mode) | 0 - 3,800 | | | | | | | | | | | | | | | | | |
| Drill chuck | SDS-plus type | | | | | | | | | | | | | | | | | |
| 18V 14.4V | EY 78A1 X (BLACK EDITION) <ul style="list-style-type: none"> Such as EY 78A1 LJ2G / PN2G Without battery and charger Compatible with the following batteries 18V: EY 9L54 B, EY 9L53 B, EY 9L52 B, EY 9L51 B, EY 9L50 B 14.4V: EY 9L47 B, EY 9L45 B, EY 9L44 B, EY 9L42 B | <table border="1"> <tr><td>Voltage</td><td>18 / 14.4V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>Depending on battery</td></tr> <tr><td>Charging time with EY 9L54 B (usable / full)</td><td>65 / 80min.</td></tr> <tr><td>Weight (incl. battery EY 9L54 B)</td><td>2.6kg</td></tr> <tr><td>Speed at no load with EY 9L54 B in min⁻¹ (rpm)</td><td>0 - 1,250</td></tr> <tr><td>Blows per minute with EY 9L54 B (soft / hard mode)</td><td>0 - 4,750</td></tr> <tr><td>Drill chuck</td><td>SDS-plus type</td></tr> </table> | Voltage | 18 / 14.4V | Battery capacity accord. to IEC (technology) | Depending on battery | Charging time with EY 9L54 B (usable / full) | 65 / 80min. | Weight (incl. battery EY 9L54 B) | 2.6kg | Speed at no load with EY 9L54 B in min ⁻¹ (rpm) | 0 - 1,250 | Blows per minute with EY 9L54 B (soft / hard mode) | 0 - 4,750 | Drill chuck | SDS-plus type | | |
| Voltage | 18 / 14.4V | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | Depending on battery | | | | | | | | | | | | | | | | | |
| Charging time with EY 9L54 B (usable / full) | 65 / 80min. | | | | | | | | | | | | | | | | | |
| Weight (incl. battery EY 9L54 B) | 2.6kg | | | | | | | | | | | | | | | | | |
| Speed at no load with EY 9L54 B in min ⁻¹ (rpm) | 0 - 1,250 | | | | | | | | | | | | | | | | | |
| Blows per minute with EY 9L54 B (soft / hard mode) | 0 - 4,750 | | | | | | | | | | | | | | | | | |
| Drill chuck | SDS-plus type | | | | | | | | | | | | | | | | | |

SDS-PLUS ROTARY HAMMER – BATTERY CAPACITIES

| VOLTAGE | | 28.8V | |
|-----------------|--------------------|-----------------|-----|
| MODEL | | EY 7880 LP2C | |
| BATTERY | | EY 9L82 B(LP) | |
| Hammer Drilling | Holes in concrete* | Ø 3.5mm x 30mm | 120 |
| | | Ø 6mm x 30mm | 150 |
| | | Ø 8mm x 100mm | 30 |
| | | Ø 12.5mm x 40mm | 70 |
| | | Ø 14.5mm x 90mm | 20 |
| | | Ø 20mm x 40mm | 30 |

Depending on test condition, the measurement result is sometimes different to that of operation manual. The table shows average values of working capacity per fully charged battery.
* At concrete strength of medium hardness

SDS-PLUS ROTARY HAMMER – BATTERY CAPACITIES

| VOLTAGE | | | 18V | 18V |
|----------------------|--|-----------------|---------------|---------------|
| MODEL | | | EY 78A1 LJ2G | EY 78A1 PN2G |
| BATTERY | | | EY 9L54 B(LJ) | EY 9L53 B(PN) |
| Drilling + fastening | Holes in concrete and screw fastened | Ø 3.5mm x 30mm | Approx. 230 | Approx. 140 |
| | Holes in concrete (plastic anchor fastening application) | Ø 6mm x 30mm | Approx. 170 | Approx. 100 |
| Hammer drilling | Holes in concrete | Ø 3.5mm x 30mm | Approx. 280 | Approx. 170 |
| | | Ø 8mm x 30mm | Approx. 150 | Approx. 90 |
| | | Ø 10mm x 40mm | Approx. 100 | Approx. 60 |
| | | Ø 12.5mm x 40mm | Approx. 50 | Approx. 30 |
| Drilling | Holes in wood | Ø 18mm t=120mm | Approx. 110 | Approx. 70 |
| | Holes in metal | Ø 13mm t=1.6mm | Approx. 170 | Approx. 100 |
| | Holes with hole saws | Ø 21mm t=1.6mm | Approx. 50 | Approx. 30 |

SAWS

| VOLTAGE (V) / CAPACITY (AH) | MODEL / FEATURES | | | | | | | | | | | | | | | | | |
|---|---|--|---------|------------|--|----------------------|--|-------------|----------------------------------|---------------|---|-------|--|-------|------------------------------|-------|------------------------------|-------|
| NEW 18V / 5.0Ah | EY 45A1 LJ2G <ul style="list-style-type: none"> High-performance 4.2Ah Li-ion battery pack Cordless Reciprocating Saw 65min. usable and 80min. full charging Light weight 3.4kg (incl. battery) Counter balance mechanism for reduced vibration For metal, plastic and wood Electronic stroke rate stabilization Incl. second battery pack | <table border="1"> <tr><td>Voltage</td><td>18V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>5.0Ah (Li-ion)</td></tr> <tr><td>Charging time (usable / full)</td><td>65 / 80min.</td></tr> <tr><td>Battery</td><td>2 x EY 9L54 B</td></tr> <tr><td>Weight (incl. battery)</td><td>3.4kg</td></tr> <tr><td>Stroke per minute in min⁻¹ (rpm)</td><td>2.800</td></tr> <tr><td>Stroke length</td><td>28mm</td></tr> <tr><td>Max. thickness of saw blades</td><td>1.6mm</td></tr> </table> | Voltage | 18V | Battery capacity accord. to IEC (technology) | 5.0Ah (Li-ion) | Charging time (usable / full) | 65 / 80min. | Battery | 2 x EY 9L54 B | Weight (incl. battery) | 3.4kg | Stroke per minute in min ⁻¹ (rpm) | 2.800 | Stroke length | 28mm | Max. thickness of saw blades | 1.6mm |
| Voltage | 18V | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 5.0Ah (Li-ion) | | | | | | | | | | | | | | | | | |
| Charging time (usable / full) | 65 / 80min. | | | | | | | | | | | | | | | | | |
| Battery | 2 x EY 9L54 B | | | | | | | | | | | | | | | | | |
| Weight (incl. battery) | 3.4kg | | | | | | | | | | | | | | | | | |
| Stroke per minute in min ⁻¹ (rpm) | 2.800 | | | | | | | | | | | | | | | | | |
| Stroke length | 28mm | | | | | | | | | | | | | | | | | |
| Max. thickness of saw blades | 1.6mm | | | | | | | | | | | | | | | | | |
| 18V / 14.4V | EY 45A1 X <ul style="list-style-type: none"> Such as EY 45A1 LJ2G Without battery and charger Compatible with the following batteries 18V: EY 9L54 B, EY 9L53 B, EY 9L52 B, EY 9L51 B, EY 9L50 B 14.4V: EY 9L47 B, EY 9L45 B, EY 9L44 B, EY 9L42 B | <table border="1"> <tr><td>Voltage</td><td>18 / 14.4V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>Depending on battery</td></tr> <tr><td>Charging time with EY 9L54 B (usable / full)</td><td>65 / 80min.</td></tr> <tr><td>Weight (incl. battery EY 9L54 B)</td><td>3.4kg</td></tr> <tr><td>Stroke per minute with EY 9L54 B in min⁻¹ (rpm)</td><td>2.800</td></tr> <tr><td>Stroke length</td><td>28mm</td></tr> <tr><td>Max. thickness of saw blades</td><td>1.6mm</td></tr> </table> | Voltage | 18 / 14.4V | Battery capacity accord. to IEC (technology) | Depending on battery | Charging time with EY 9L54 B (usable / full) | 65 / 80min. | Weight (incl. battery EY 9L54 B) | 3.4kg | Stroke per minute with EY 9L54 B in min ⁻¹ (rpm) | 2.800 | Stroke length | 28mm | Max. thickness of saw blades | 1.6mm | | |
| Voltage | 18 / 14.4V | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | Depending on battery | | | | | | | | | | | | | | | | | |
| Charging time with EY 9L54 B (usable / full) | 65 / 80min. | | | | | | | | | | | | | | | | | |
| Weight (incl. battery EY 9L54 B) | 3.4kg | | | | | | | | | | | | | | | | | |
| Stroke per minute with EY 9L54 B in min ⁻¹ (rpm) | 2.800 | | | | | | | | | | | | | | | | | |
| Stroke length | 28mm | | | | | | | | | | | | | | | | | |
| Max. thickness of saw blades | 1.6mm | | | | | | | | | | | | | | | | | |
| NEW 18V / 5.0Ah | EY 45A2 LJ2G <ul style="list-style-type: none"> High-performance 5.0Ah Li-ion battery pack Cordless Multi Purpose Cutter with ergonomic design Light weight 2.8kg (incl. battery) Metal Cutter Blade as standard accessory For metal, plastic and wood Electric speed control 3-way dust control system Incl. second battery pack | <table border="1"> <tr><td>Voltage</td><td>18V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>5.0Ah (Li-ion)</td></tr> <tr><td>Charging time (usable / full)</td><td>65 / 80min.</td></tr> <tr><td>Battery</td><td>2 x EY 9L54 B</td></tr> <tr><td>Weight (incl. battery)</td><td>2.8kg</td></tr> <tr><td>Speed at no load in min⁻¹ (rpm)</td><td>4.500</td></tr> <tr><td>Max. cutting depth</td><td>46mm</td></tr> <tr><td>Blade size (outer diameter)</td><td>135mm</td></tr> </table> | Voltage | 18V | Battery capacity accord. to IEC (technology) | 5.0Ah (Li-ion) | Charging time (usable / full) | 65 / 80min. | Battery | 2 x EY 9L54 B | Weight (incl. battery) | 2.8kg | Speed at no load in min ⁻¹ (rpm) | 4.500 | Max. cutting depth | 46mm | Blade size (outer diameter) | 135mm |
| Voltage | 18V | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 5.0Ah (Li-ion) | | | | | | | | | | | | | | | | | |
| Charging time (usable / full) | 65 / 80min. | | | | | | | | | | | | | | | | | |
| Battery | 2 x EY 9L54 B | | | | | | | | | | | | | | | | | |
| Weight (incl. battery) | 2.8kg | | | | | | | | | | | | | | | | | |
| Speed at no load in min ⁻¹ (rpm) | 4.500 | | | | | | | | | | | | | | | | | |
| Max. cutting depth | 46mm | | | | | | | | | | | | | | | | | |
| Blade size (outer diameter) | 135mm | | | | | | | | | | | | | | | | | |
| 18V / 14.4V | EY 45A2 XM <ul style="list-style-type: none"> Such as EY 45A2 LJ2G 135mm blade for metal as standard accessories Without battery and charger Compatible with the following batteries 18V: EY 9L54 B, EY 9L53 B, EY 9L52 B, EY 9L51 B, EY 9L50 B 14.4V: EY 9L47 B, EY 9L45 B, EY 9L44 B, EY 9L42 B | <table border="1"> <tr><td>Voltage</td><td>18 / 14.4V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>Depending on battery</td></tr> <tr><td>Charging time with EY 9L54 B (usable / full)</td><td>65 / 80min.</td></tr> <tr><td>Weight (incl. battery EY 9L54 B)</td><td>2.8kg</td></tr> <tr><td>Speed at no load with EY 9L54 B in min⁻¹ (rpm)</td><td>4.500</td></tr> <tr><td>Max. cutting depth</td><td>46mm</td></tr> <tr><td>Blade size (outer diameter)</td><td>135mm</td></tr> </table> | Voltage | 18 / 14.4V | Battery capacity accord. to IEC (technology) | Depending on battery | Charging time with EY 9L54 B (usable / full) | 65 / 80min. | Weight (incl. battery EY 9L54 B) | 2.8kg | Speed at no load with EY 9L54 B in min ⁻¹ (rpm) | 4.500 | Max. cutting depth | 46mm | Blade size (outer diameter) | 135mm | | |
| Voltage | 18 / 14.4V | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | Depending on battery | | | | | | | | | | | | | | | | | |
| Charging time with EY 9L54 B (usable / full) | 65 / 80min. | | | | | | | | | | | | | | | | | |
| Weight (incl. battery EY 9L54 B) | 2.8kg | | | | | | | | | | | | | | | | | |
| Speed at no load with EY 9L54 B in min ⁻¹ (rpm) | 4.500 | | | | | | | | | | | | | | | | | |
| Max. cutting depth | 46mm | | | | | | | | | | | | | | | | | |
| Blade size (outer diameter) | 135mm | | | | | | | | | | | | | | | | | |
| 18V / 14.4V | EY 45A2 XW <ul style="list-style-type: none"> Such as EY 45A2 LJ2G 135mm blade for wood as standard accessories Without battery and charger Compatible with the following batteries 18V: EY 9L54 B, EY 9L53 B, EY 9L52 B, EY 9L51 B, EY 9L50 B 14.4V: EY 9L47 B, EY 9L45 B, EY 9L44 B, EY 9L42 B | <table border="1"> <tr><td>Voltage</td><td>18 / 14.4V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>Depending on battery</td></tr> <tr><td>Charging time with EY 9L54 B (usable / full)</td><td>65 / 80min.</td></tr> <tr><td>Weight (incl. battery EY 9L54 B)</td><td>2.8kg</td></tr> <tr><td>Speed at no load with EY 9L54 B in min⁻¹ (rpm)</td><td>4.500</td></tr> <tr><td>Max. cutting depth</td><td>46mm</td></tr> <tr><td>Blade size (outer diameter)</td><td>135mm</td></tr> </table> | Voltage | 18 / 14.4V | Battery capacity accord. to IEC (technology) | Depending on battery | Charging time with EY 9L54 B (usable / full) | 65 / 80min. | Weight (incl. battery EY 9L54 B) | 2.8kg | Speed at no load with EY 9L54 B in min ⁻¹ (rpm) | 4.500 | Max. cutting depth | 46mm | Blade size (outer diameter) | 135mm | | |
| Voltage | 18 / 14.4V | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | Depending on battery | | | | | | | | | | | | | | | | | |
| Charging time with EY 9L54 B (usable / full) | 65 / 80min. | | | | | | | | | | | | | | | | | |
| Weight (incl. battery EY 9L54 B) | 2.8kg | | | | | | | | | | | | | | | | | |
| Speed at no load with EY 9L54 B in min ⁻¹ (rpm) | 4.500 | | | | | | | | | | | | | | | | | |
| Max. cutting depth | 46mm | | | | | | | | | | | | | | | | | |
| Blade size (outer diameter) | 135mm | | | | | | | | | | | | | | | | | |

SAWS

| VOLTAGE (V) / CAPACITY (AH) | MODEL / FEATURES | | |
|-----------------------------|--|---|---|
| 18V |  <p>EY 4550 X</p> <ul style="list-style-type: none"> ■ Cordless Jigsaw with 4 stage pendulum ■ Light weight 3.35kg (incl. battery) ■ Cutting angle adjustment (0-45°) ■ Simple blade change mechanism ■ For metal, plastic and wood ■ Without battery and charger ■ Compatible with the following batteries <p>18V: EY 9L54 B, EY 9L53 B, EY 9L52 B, EY 9L51 B, EY 9L50 B</p> | <p>Voltage</p> <p>Battery capacity accord. to IEC (technology)</p> <p>Charging time with EY 9L54 B (usable / full)</p> <p>Weight (incl. battery EY 9L54 B)</p> <p>Stroke per minute with EY 9L54 B in min⁻¹ (rpm)</p> <p>Max. cutting depth</p> <p>Blade size (outer diameter)</p> | <p>18V</p> <p>Depending on battery</p> <p>65 / 80min.</p> <p>3.35kg</p> <p>2.500</p> <p>65mm</p> <p>26mm</p> |
| 14.4V 4.2Ah |  <p>EY 4541 LS1S</p> <ul style="list-style-type: none"> ■ High-performance 4.2Ah Li-ion battery pack ■ Cordless Jigsaw with 4 cutting movements ■ Light weight 2.25kg (incl. battery) ■ Cutting angle adjustment (0-45°) ■ For metal, plastic and wood ■ Electronic stroke rate stabilization ■ Dust blow function ■ Incl. one battery pack | <p>Voltage</p> <p>Battery capacity accord. to IEC (technology)</p> <p>Charging time (usable / full)</p> <p>Battery</p> <p>Weight (incl. battery)</p> <p>Stroke per minute in min⁻¹ (rpm)</p> <p>Max. cutting depth</p> <p>Blade size (outer diameter)</p> | <p>14.4V</p> <p>4.2Ah (Li-ion)</p> <p>50 / 60min.</p> <p>1 x EY 9L45 B</p> <p>2.25kg</p> <p>2.400</p> <p>65mm</p> <p>20mm</p> |
| 14.4V |  <p>EY 4541 X</p> <ul style="list-style-type: none"> ■ Such as EY 4541 LS1S ■ Without battery and charger ■ Compatible with the following batteries <p>14.4V: EY 9L47 B, EY 9L45 B, EY 9L44 B, EY 9L42 B</p> | <p>Voltage</p> <p>Battery capacity accord. to IEC (technology)</p> <p>Charging time with EY 9L45 B (usable / full)</p> <p>Weight (incl. battery EY 9L45 B)</p> <p>Stroke per minute with EY 9L45 B in min⁻¹ (rpm)</p> <p>Max. cutting depth</p> <p>Blade size (outer diameter)</p> | <p>14.4V</p> <p>Depending on battery</p> <p>50 / 60min.</p> <p>2.25kg</p> <p>2.400</p> <p>65mm</p> <p>20mm</p> |

SAWS – BATTERY CAPACITIES

| VOLTAGE | | | 18V |
|-----------------------|--------------------------------|---------------------------------|---------------------------|
| MODEL | | | EY 45A1 LJ2G |
| BATTERY | | | EY 9L54 B(LJ) |
| Sawing | Steel pipe for ordinary piping | Outer diameter 34mm (t=3.2mm) | Approx. 55 cut per charge |
| | | Outer diameter 48.6mm (t=3.5mm) | Approx. 35 cut per charge |
| | | Outer diameter 89.1mm (t=4.2mm) | Approx. 11 cut per charge |
| | Yellow pine | 2 x 4mm (38 x 89mm) | Approx. 90 cut per charge |
| 2 x 10mm (38 x 235mm) | | Approx. 55 cut per charge | |

| VOLTAGE | | | 18V |
|------------------|-------------------------|-----------------------------------|----------------------------|
| MODEL | | | EY 45A2 LJ2G |
| BATTERY | | | EY 9L54 B(LJ) |
| Sawing / Cutting | Metal (EY 9PM13 E) | Conduit pipe outer 25.4mm t=1.2mm | Approx. 340 cut per charge |
| | | Water pipe (PVC) 34mm t=4.7mm | Approx. 70 cut per charge |
| | Thin metal (EY 9PM13 F) | SPC 450mm t=1.6mm | Approx. 25 cut per charge |
| | Wood (EY 9PW13 C) | Squared log 45 x 45mm | Approx. 300 cut per charge |
| | | Squared log 2 x 10, 38 x 235mm | Approx. 280 cut per charge |
| | Thin wood (EY 9PW13 D) | Plywood 900mm t=12mm | Approx. 120 cut per charge |
| | | Plywood 900mm t=5mm | Approx. 320 cut per charge |

| VOLTAGE | | | 18V | 14.4V |
|---------|----------------|------------|---------------|---------------|
| MODEL | | | EY 4550 X | EY 4541 LS1S |
| BATTERY | | | EY 9L51 B(LS) | EY 9L45 B(LS) |
| Sawing | Plywood | 12mm, 15mm | 23m | 10m |
| | Particle board | t=20mm x 2 | 13m | 7m |

BLADES

| | MODEL / FEATURES | | |
|---|---|--|--|
|  | EY 9 PW 17 A <ul style="list-style-type: none"> ■ 165mm diameter Carbide-tipped blade for wood ■ 48 tooth count for EY 3551 | | |
|  | EY 9 PW 13 C <ul style="list-style-type: none"> ■ 135mm diameter Carbide-tipped blade for wood ■ 24 tooth count for EY 3503, EY 45A2 and EY 4542 | | |
|  | EY 9 PW 13 D <ul style="list-style-type: none"> ■ 135mm diameter Carbide-tipped blade for wood ■ 48 tooth count for EY 3503, EY 45A2 and EY 4542 | | |
|  | EY 9 PP 13 B <ul style="list-style-type: none"> ■ 135mm diameter Plastic saw blade ■ 52 tooth count for EY 45A2 and EY 4542 | | |
|  | EY 9 PM 17 B <ul style="list-style-type: none"> ■ 165mm diameter Metal saw blade ■ 56 tooth count for EY 3552 | | |
|  | EY 9 PM 17 A <ul style="list-style-type: none"> ■ 165mm diameter Metal saw blade ■ 40 tooth count for EY 3552 | | |
|  | EY 9 PM 13 E <ul style="list-style-type: none"> ■ 135mm diameter Metal saw blade ■ 30 tooth count for EY 3503, EY 45A2 and EY 4542 | | |
|  | EY 9 PM 13 F <ul style="list-style-type: none"> ■ 135mm diameter Metal saw blade ■ 50 tooth count for EY 3503, EY 45A2 and EY 4542 | | |
|  | EY 9 PM 11 D <ul style="list-style-type: none"> ■ 110mm diameter Metal saw blade ■ 40 tooth count for EY 3501 | | |
|  | EY 9 PM 11 C <ul style="list-style-type: none"> ■ 110mm diameter Metal saw blade ■ 24 tooth count for EY 3501 | | |
|  | EY 9 PG 11 A <ul style="list-style-type: none"> ■ 110mm diameter Diamond weel ■ Cutting glass and tiles for EY 3550 | | |

ANGLE GRINDER

NEW

| VOLTAGE (V) / CAPACITY (AH) | MODEL / FEATURES | | | | | | | | | | | | | | | |
|--|--|---|---------|------------|--|----------------------|--|-------------|----------------------------------|---------------|--|--------|---|--------|----------------------------|-------|
| 18V 5.0Ah | EY 46A2 LJ2G <ul style="list-style-type: none"> High-performance 5.0Ah Li-ion battery pack Light weight 2.35kg (incl. battery) For 125mm discs Spindle lock for easy disc changes Safety function, when battery is inserted at switch 'on' Re-start function For hardly accessible places Incl. second battery pack | <table border="1"> <tr><td>Voltage</td><td>18V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>5.0Ah (Li-ion)</td></tr> <tr><td>Charging time (usable / full)</td><td>65 / 80min.</td></tr> <tr><td>Battery</td><td>2 x EY 9L54 B</td></tr> <tr><td>Weight (incl. battery)</td><td>2.35kg</td></tr> <tr><td>Speed at no load in min⁻¹ (rpm)</td><td>10.000</td></tr> <tr><td>Disc size (outer diameter)</td><td>125mm</td></tr> </table> | Voltage | 18V | Battery capacity accord. to IEC (technology) | 5.0Ah (Li-ion) | Charging time (usable / full) | 65 / 80min. | Battery | 2 x EY 9L54 B | Weight (incl. battery) | 2.35kg | Speed at no load in min ⁻¹ (rpm) | 10.000 | Disc size (outer diameter) | 125mm |
| Voltage | 18V | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 5.0Ah (Li-ion) | | | | | | | | | | | | | | | |
| Charging time (usable / full) | 65 / 80min. | | | | | | | | | | | | | | | |
| Battery | 2 x EY 9L54 B | | | | | | | | | | | | | | | |
| Weight (incl. battery) | 2.35kg | | | | | | | | | | | | | | | |
| Speed at no load in min ⁻¹ (rpm) | 10.000 | | | | | | | | | | | | | | | |
| Disc size (outer diameter) | 125mm | | | | | | | | | | | | | | | |
| 18V / 14.4V | EY 46A2 X <ul style="list-style-type: none"> Such as EY 46A2 LJ2G Without battery and charger Compatible with the following batteries 18V: EY 9L54 B, EY 9L53 B, EY 9L52 B, EY 9L51 B, EY 9L50 B 14.4V: EY 9L47 B, EY 9L45 B, EY 9L44 B, EY 9L42 B | <table border="1"> <tr><td>Voltage</td><td>18 / 14.4V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>Depending on battery</td></tr> <tr><td>Charging time with EY 9L54 B (usable / full)</td><td>65 / 80min.</td></tr> <tr><td>Weight (incl. battery EY 9L54 B)</td><td>2.35kg</td></tr> <tr><td>Speed at no load with EY 9L54 B in min⁻¹ (rpm)</td><td>10.000</td></tr> <tr><td>Disc size (outer diameter)</td><td>125mm</td></tr> </table> | Voltage | 18 / 14.4V | Battery capacity accord. to IEC (technology) | Depending on battery | Charging time with EY 9L54 B (usable / full) | 65 / 80min. | Weight (incl. battery EY 9L54 B) | 2.35kg | Speed at no load with EY 9L54 B in min ⁻¹ (rpm) | 10.000 | Disc size (outer diameter) | 125mm | | |
| Voltage | 18 / 14.4V | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | Depending on battery | | | | | | | | | | | | | | | |
| Charging time with EY 9L54 B (usable / full) | 65 / 80min. | | | | | | | | | | | | | | | |
| Weight (incl. battery EY 9L54 B) | 2.35kg | | | | | | | | | | | | | | | |
| Speed at no load with EY 9L54 B in min ⁻¹ (rpm) | 10.000 | | | | | | | | | | | | | | | |
| Disc size (outer diameter) | 125mm | | | | | | | | | | | | | | | |

ANGLE GRINDER – BATTERY CAPACITIES

| VOLTAGE | | 18V |
|---------|-----------------|------------------------------|
| MODEL | | EY 46A2 LJ2G |
| BATTERY | | EY 9L54 B(LJ) |
| | Reinforcing bar | Ø 10mm |
| | | Approx. 140pcs / charge |
| | Mild steel | W 3/8 Continuous thread stud |
| | | Approx. 180pcs / charge |

SEALING GUN

| VOLTAGE (V) / CAPACITY (AH) | MODEL / FEATURES | | | | | | | | | | | | | |
|--|---|--|---------|-------|--|----------------------|--|-------------|----------------------------------|---------------|---------------------------------|-----------------|------------------|-----------------|
| 14.4V 4.2Ah | EY 3641 LS1S <ul style="list-style-type: none"> High-performance 4.2Ah Li-ion battery pack Light weight 2.8kg (incl. battery) For cartridge and foil pack up to 600ml Electric speed control Fully automatic decompression Incl. one battery pack* | <table border="1"> <tr><td>Voltage</td><td>14.4V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>4.2Ah (Li-ion)</td></tr> <tr><td>Charging time (usable / full)</td><td>50 / 60min.</td></tr> <tr><td>Battery</td><td>1 x EY 9L45 B</td></tr> <tr><td>Weight (incl. battery)</td><td>2.8kg</td></tr> <tr><td>Pushing pressure</td><td>4,410N (450kgf)</td></tr> </table> | Voltage | 14.4V | Battery capacity accord. to IEC (technology) | 4.2Ah (Li-ion) | Charging time (usable / full) | 50 / 60min. | Battery | 1 x EY 9L45 B | Weight (incl. battery) | 2.8kg | Pushing pressure | 4,410N (450kgf) |
| Voltage | 14.4V | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 4.2Ah (Li-ion) | | | | | | | | | | | | | |
| Charging time (usable / full) | 50 / 60min. | | | | | | | | | | | | | |
| Battery | 1 x EY 9L45 B | | | | | | | | | | | | | |
| Weight (incl. battery) | 2.8kg | | | | | | | | | | | | | |
| Pushing pressure | 4,410N (450kgf) | | | | | | | | | | | | | |
| 14.4V | EY 3641 K <ul style="list-style-type: none"> Such as EY 3641 LS1S Incl. plastic box, without battery and charger Compatible with the following batteries 14.4V: EY 9L47 B, EY 9L45 B, EY 9L44 B, EY 9L42 B | <table border="1"> <tr><td>Voltage</td><td>14.4V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>Depending on battery</td></tr> <tr><td>Charging time with EY 9L45 B (usable / full)</td><td>50 / 60min.</td></tr> <tr><td>Weight (incl. battery EY 9L45 B)</td><td>2.8kg</td></tr> <tr><td>Pushing pressure with EY 9L45 B</td><td>4,410N (450kgf)</td></tr> </table> | Voltage | 14.4V | Battery capacity accord. to IEC (technology) | Depending on battery | Charging time with EY 9L45 B (usable / full) | 50 / 60min. | Weight (incl. battery EY 9L45 B) | 2.8kg | Pushing pressure with EY 9L45 B | 4,410N (450kgf) | | |
| Voltage | 14.4V | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | Depending on battery | | | | | | | | | | | | | |
| Charging time with EY 9L45 B (usable / full) | 50 / 60min. | | | | | | | | | | | | | |
| Weight (incl. battery EY 9L45 B) | 2.8kg | | | | | | | | | | | | | |
| Pushing pressure with EY 9L45 B | 4,410N (450kgf) | | | | | | | | | | | | | |
| 14.4V 4.2Ah | EY 3640 LS1S <ul style="list-style-type: none"> High-performance 4.2Ah Li-ion battery pack Light weight 2.65kg (incl. battery) For 310ml cartridge Electric speed control Fully automatic decompression Incl. one battery pack | <table border="1"> <tr><td>Voltage</td><td>14.4V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>4.2Ah (Li-ion)</td></tr> <tr><td>Charging time (usable / full)</td><td>50 / 60min.</td></tr> <tr><td>Battery</td><td>1 x EY 9L45 B</td></tr> <tr><td>Weight (incl. battery)</td><td>2.65kg</td></tr> <tr><td>Pushing pressure</td><td>4,410N (450kgf)</td></tr> </table> | Voltage | 14.4V | Battery capacity accord. to IEC (technology) | 4.2Ah (Li-ion) | Charging time (usable / full) | 50 / 60min. | Battery | 1 x EY 9L45 B | Weight (incl. battery) | 2.65kg | Pushing pressure | 4,410N (450kgf) |
| Voltage | 14.4V | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 4.2Ah (Li-ion) | | | | | | | | | | | | | |
| Charging time (usable / full) | 50 / 60min. | | | | | | | | | | | | | |
| Battery | 1 x EY 9L45 B | | | | | | | | | | | | | |
| Weight (incl. battery) | 2.65kg | | | | | | | | | | | | | |
| Pushing pressure | 4,410N (450kgf) | | | | | | | | | | | | | |

SEALING GUN

| VOLTAGE (V) / CAPACITY (AH) | MODEL / FEATURES | | | | | | | | | | | | | | |
|--|--|---|---|---------|-------|--|----------------------|--|-------------|----------------------------------|---------------|---------------------------------|-----------------|------------------|-----------------|
| 14.4V | EY 3640 K <ul style="list-style-type: none"> Such as EY 3640 LS1S Incl. plastic box, without battery and charger Compatible with the following batteries 14.4V: EY 9L47 B, EY 9L45 B, EY 9L44 B, EY 9L42 B |  | <table border="1"> <tr><td>Voltage</td><td>14.4V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>Depending on battery</td></tr> <tr><td>Charging time with EY 9L45 B (usable / full)</td><td>50 / 60min.</td></tr> <tr><td>Weight (incl. battery EY 9L45 B)</td><td>2.65kg</td></tr> <tr><td>Pushing pressure with EY 9L45 B</td><td>4,410N (450kgf)</td></tr> </table> | Voltage | 14.4V | Battery capacity accord. to IEC (technology) | Depending on battery | Charging time with EY 9L45 B (usable / full) | 50 / 60min. | Weight (incl. battery EY 9L45 B) | 2.65kg | Pushing pressure with EY 9L45 B | 4,410N (450kgf) | | |
| Voltage | 14.4V | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | Depending on battery | | | | | | | | | | | | | | |
| Charging time with EY 9L45 B (usable / full) | 50 / 60min. | | | | | | | | | | | | | | |
| Weight (incl. battery EY 9L45 B) | 2.65kg | | | | | | | | | | | | | | |
| Pushing pressure with EY 9L45 B | 4,410N (450kgf) | | | | | | | | | | | | | | |
| 3.6V 1.5Ah | EY 3610 LA1J <ul style="list-style-type: none"> 1.5Ah Li-ion battery pack Light weight 2.15kg (incl. battery) Double extending rack keeps body compact For cartridge and foil pack up to 400ml Electric speed control Fully automatic decompression Incl. one battery pack |  | <table border="1"> <tr><td>Voltage</td><td>3.6V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>1.5Ah (Li-ion)</td></tr> <tr><td>Charging time (usable / full)</td><td>15 / 30min.</td></tr> <tr><td>Battery</td><td>1 x EY 9L10 B</td></tr> <tr><td>Weight (incl. battery)</td><td>2.15kg</td></tr> <tr><td>Pushing pressure</td><td>2,450N (250kgf)</td></tr> </table> | Voltage | 3.6V | Battery capacity accord. to IEC (technology) | 1.5Ah (Li-ion) | Charging time (usable / full) | 15 / 30min. | Battery | 1 x EY 9L10 B | Weight (incl. battery) | 2.15kg | Pushing pressure | 2,450N (250kgf) |
| Voltage | 3.6V | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | 1.5Ah (Li-ion) | | | | | | | | | | | | | | |
| Charging time (usable / full) | 15 / 30min. | | | | | | | | | | | | | | |
| Battery | 1 x EY 9L10 B | | | | | | | | | | | | | | |
| Weight (incl. battery) | 2.15kg | | | | | | | | | | | | | | |
| Pushing pressure | 2,450N (250kgf) | | | | | | | | | | | | | | |

SEALING GUN – BATTERY CAPACITIES

| VOLTAGE | | 14.4V | 3.6V | |
|---------|-------------|---------------|---------------|----------------|
| MODEL | | EY 3640 LS1S* | EY 3641 LS1S* | EY 3610 LA1J** |
| | Silicone | 380 | 380 | 50 |
| | Acrylic | 410 | 410 | 50 |
| | Polyethelen | 190 | 190 | 30 |

Depending on test condition, the measurement result is sometimes different to that of operation manual. The table shows average values of working capacity per fully charged battery.

* Temperature 20°C Ø 5mm cutting hole, 310ml cartridge

** Temperature 20°C Ø 5mm cutting hole, Silicone: Sikaflex-M1 320ml cartridge, Acrylic: Konishi 330ml cartridge, Polyethelen: Sikaflex-221 320ml cartridge

BLOWER, VACUUM CLEANER, FLASHLIGHT, AND RADIO

| VOLTAGE (V) / CAPACITY (AH) | MODEL / FEATURES | | | | | | | | | | | | | | |
|--|---|---|--|---------|-------------------|--|----------------------|------------------------|--------|--------------------------------------|---------------------|--|--------------------|---|--------------------------------------|
| 18V / 14.4V | EY 37A1 B <ul style="list-style-type: none"> Suitable for all 18 / 14.4V Li-ion battery packs Light weight 1.2kg (excl. battery pack) Max. air speed 70m/s Hours of use with EY 9L45 B (14.4V) approx. 22min. Max. air volume 3m³ Dual voltage Without battery and charger |  | <table border="1"> <tr><td>Voltage</td><td>18 / 14.4V</td></tr> <tr><td>Battery capacity accord. to IEC</td><td>Depending on battery</td></tr> <tr><td>Weight (excl. battery)</td><td>1.2kg</td></tr> <tr><td>Hours of use (EY 9L51 B / EY 9L45 B)</td><td>Approx. 15 / 22min.</td></tr> <tr><td>Max. air speed (EY 9L51 B / EY 9L45 B)</td><td>Approx. 70 / 60m/s</td></tr> <tr><td>Max. air volume (EY 9L51 B / EY 9L45 B)</td><td>Approx. 3 / 2,6 m³/min.</td></tr> </table> | Voltage | 18 / 14.4V | Battery capacity accord. to IEC | Depending on battery | Weight (excl. battery) | 1.2kg | Hours of use (EY 9L51 B / EY 9L45 B) | Approx. 15 / 22min. | Max. air speed (EY 9L51 B / EY 9L45 B) | Approx. 70 / 60m/s | Max. air volume (EY 9L51 B / EY 9L45 B) | Approx. 3 / 2,6 m ³ /min. |
| Voltage | 18 / 14.4V | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC | Depending on battery | | | | | | | | | | | | | | |
| Weight (excl. battery) | 1.2kg | | | | | | | | | | | | | | |
| Hours of use (EY 9L51 B / EY 9L45 B) | Approx. 15 / 22min. | | | | | | | | | | | | | | |
| Max. air speed (EY 9L51 B / EY 9L45 B) | Approx. 70 / 60m/s | | | | | | | | | | | | | | |
| Max. air volume (EY 9L51 B / EY 9L45 B) | Approx. 3 / 2,6 m ³ /min. | | | | | | | | | | | | | | |
| 14.4V | EY 3743 B <ul style="list-style-type: none"> Suitable for all 14.4V Li-ion battery packs Light weight 0.94kg (excl. battery pack) Dust storage 180ml Noise 74 dB(A) Run time of use with EY 9L45 B Level 1: 37min. and level 2: 52min. Accessories nozzles 4 Without battery and charger |  | <table border="1"> <tr><td>Voltage</td><td>14.4V</td></tr> <tr><td>Battery capacity accord. to IEC (technology)</td><td>Depending on battery</td></tr> <tr><td>Weight (excl. battery)</td><td>0.94kg</td></tr> </table> | Voltage | 14.4V | Battery capacity accord. to IEC (technology) | Depending on battery | Weight (excl. battery) | 0.94kg | | | | | | |
| Voltage | 14.4V | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC (technology) | Depending on battery | | | | | | | | | | | | | | |
| Weight (excl. battery) | 0.94kg | | | | | | | | | | | | | | |
| 21.6V / 18V / 14.4V | EY 37C1 B <ul style="list-style-type: none"> Suitable for all 21.6 / 18 / 14.4V Li-ion battery packs Light weight 0.34kg (excl. battery pack) Hours of use with EY 9L45 B (14.4V) approx. 5h 10min. Adjustable head angle (four steps) Brightness of approx. 4,000 Lux with Xenon 0.7A bulb Shoulder strap and low battery indication Without battery and charger |  | <table border="1"> <tr><td>Voltage</td><td>21.6 / 18 / 14.4V</td></tr> <tr><td>Battery capacity accord. to IEC</td><td>Depending on battery</td></tr> <tr><td>Weight (excl. battery)</td><td>0.34kg</td></tr> <tr><td>Electric light bulb</td><td>Xenon 0.7A</td></tr> <tr><td>Brightness</td><td>Approx. 4,000 Lux</td></tr> <tr><td>Hours of use with EY 9L45 B (14.4V)</td><td>Approx. 5h 10min.</td></tr> </table> | Voltage | 21.6 / 18 / 14.4V | Battery capacity accord. to IEC | Depending on battery | Weight (excl. battery) | 0.34kg | Electric light bulb | Xenon 0.7A | Brightness | Approx. 4,000 Lux | Hours of use with EY 9L45 B (14.4V) | Approx. 5h 10min. |
| Voltage | 21.6 / 18 / 14.4V | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC | Depending on battery | | | | | | | | | | | | | | |
| Weight (excl. battery) | 0.34kg | | | | | | | | | | | | | | |
| Electric light bulb | Xenon 0.7A | | | | | | | | | | | | | | |
| Brightness | Approx. 4,000 Lux | | | | | | | | | | | | | | |
| Hours of use with EY 9L45 B (14.4V) | Approx. 5h 10min. | | | | | | | | | | | | | | |

BLOWER, VACUUM CLEANER, FLASHLIGHT AND RADIO

| VOLTAGE (V) / CAPACITY (AH) | MODEL / FEATURES | | | | | | | | | | | | | | | | | | |
|--|---|---|--|--------------|---|---------------------------------|-------------------------------|------------------------|--------|---------------------|------------------------------------|---------------------------|---|-------------------------------------|---|--|-------------------|--|-------------------|
| 21.6V / 18V / 14.4V | EY 37C2 B <ul style="list-style-type: none"> ■ Suitable for all 21.6 / 18 / 14.4V Li-ion battery packs ■ Light weight 0.34kg (excl. battery pack) ■ Hours of use with EY 9L51 B (18V) approx. 15h 30min ■ Adjustable head angle (four steps) ■ Brightness of approx. 380 Lux (side surface) ■ approx. 55 Lux (top surface) ■ Shoulder strap and low battery indication ■ Without battery and charger |  | <table border="1"> <tr><td>Voltage</td><td>21.6 / 18 / 14.4V</td></tr> <tr><td>Battery capacity accord. to IEC</td><td>Depending on battery</td></tr> <tr><td>Weight (excl. battery)</td><td>0.34kg</td></tr> <tr><td>Electric light bulb</td><td>LED</td></tr> <tr><td>Brightness (side surface)</td><td>Approx. 380 Lux</td></tr> <tr><td>Brightness (top surface)</td><td>Approx. 55 Lux</td></tr> <tr><td>Hours of use with EY 9L51 B (18V) (side surface)</td><td>Approx. 17h 30min</td></tr> <tr><td>Hours of use with EY 9L51 B (18V) (entire surface)</td><td>Approx. 15h 30min</td></tr> </table> | Voltage | 21.6 / 18 / 14.4V | Battery capacity accord. to IEC | Depending on battery | Weight (excl. battery) | 0.34kg | Electric light bulb | LED | Brightness (side surface) | Approx. 380 Lux | Brightness (top surface) | Approx. 55 Lux | Hours of use with EY 9L51 B (18V) (side surface) | Approx. 17h 30min | Hours of use with EY 9L51 B (18V) (entire surface) | Approx. 15h 30min |
| Voltage | 21.6 / 18 / 14.4V | | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC | Depending on battery | | | | | | | | | | | | | | | | | | |
| Weight (excl. battery) | 0.34kg | | | | | | | | | | | | | | | | | | |
| Electric light bulb | LED | | | | | | | | | | | | | | | | | | |
| Brightness (side surface) | Approx. 380 Lux | | | | | | | | | | | | | | | | | | |
| Brightness (top surface) | Approx. 55 Lux | | | | | | | | | | | | | | | | | | |
| Hours of use with EY 9L51 B (18V) (side surface) | Approx. 17h 30min | | | | | | | | | | | | | | | | | | |
| Hours of use with EY 9L51 B (18V) (entire surface) | Approx. 15h 30min | | | | | | | | | | | | | | | | | | |
| 10.8V 1.5Ah | EY 3732 B <ul style="list-style-type: none"> ■ 1.5Ah Li-ion battery pack ■ Light weight 0.14kg (incl. battery) ■ Hours of use approx. 4h (with EY 9L32 B) ■ Brightness of approx. 540 Lux ■ Without battery and charger ■ Available only as part of twin kit |  | <table border="1"> <tr><td>Voltage</td><td>10.8V</td></tr> <tr><td>Battery capacity accord. to IEC</td><td>1.5Ah</td></tr> <tr><td>Weight (excl. battery)</td><td>0.14kg</td></tr> <tr><td>Electric light bulb</td><td>LED</td></tr> <tr><td>Brightness</td><td>Approx. 540 Lux</td></tr> <tr><td>Hours of use with EY 9L32 B (10.8V)</td><td>Approx. 4h</td></tr> </table> | Voltage | 10.8V | Battery capacity accord. to IEC | 1.5Ah | Weight (excl. battery) | 0.14kg | Electric light bulb | LED | Brightness | Approx. 540 Lux | Hours of use with EY 9L32 B (10.8V) | Approx. 4h | | | | |
| Voltage | 10.8V | | | | | | | | | | | | | | | | | | |
| Battery capacity accord. to IEC | 1.5Ah | | | | | | | | | | | | | | | | | | |
| Weight (excl. battery) | 0.14kg | | | | | | | | | | | | | | | | | | |
| Electric light bulb | LED | | | | | | | | | | | | | | | | | | |
| Brightness | Approx. 540 Lux | | | | | | | | | | | | | | | | | | |
| Hours of use with EY 9L32 B (10.8V) | Approx. 4h | | | | | | | | | | | | | | | | | | |
| 18V / 14.4V | EY 37A2 B <ul style="list-style-type: none"> ■ Large diameter speakers for clear, dynamic sound ■ Panasonic proprietary optimal tuning from low to high key ■ Bluetooth® function ■ Dynamic durability IP64 and tough protection cage ■ Tone control settings ■ FM/AM with 12 presets ■ Handy LED light function |  | <table border="1"> <tr><td>Power supply</td><td>Li-ion battery (14.4 - 18V), AC adaptor</td></tr> <tr><td>Mode</td><td>FM / AM / Bluetooth® / AUX-IN</td></tr> <tr><td>Weight (excl. battery)</td><td>4.0kg</td></tr> <tr><td>Frequency coverage</td><td>FM: 87.5-108MHz / AM: 522-1,629kHz</td></tr> <tr><td>Dust / Water Protection</td><td>IP64 (Dustproof and splashproof) with tough protection cage</td></tr> <tr><td>Operating time (18V / 14.4V)</td><td>4.2Ah (LS type): Approx. 24 hrs / 2.0Ah (LF type): Approx. 11 hrs</td></tr> <tr><td>Size (LxHxW)</td><td>344 x 280 x 239mm</td></tr> </table> | Power supply | Li-ion battery (14.4 - 18V), AC adaptor | Mode | FM / AM / Bluetooth® / AUX-IN | Weight (excl. battery) | 4.0kg | Frequency coverage | FM: 87.5-108MHz / AM: 522-1,629kHz | Dust / Water Protection | IP64 (Dustproof and splashproof) with tough protection cage | Operating time (18V / 14.4V) | 4.2Ah (LS type): Approx. 24 hrs / 2.0Ah (LF type): Approx. 11 hrs | Size (LxHxW) | 344 x 280 x 239mm | | |
| Power supply | Li-ion battery (14.4 - 18V), AC adaptor | | | | | | | | | | | | | | | | | | |
| Mode | FM / AM / Bluetooth® / AUX-IN | | | | | | | | | | | | | | | | | | |
| Weight (excl. battery) | 4.0kg | | | | | | | | | | | | | | | | | | |
| Frequency coverage | FM: 87.5-108MHz / AM: 522-1,629kHz | | | | | | | | | | | | | | | | | | |
| Dust / Water Protection | IP64 (Dustproof and splashproof) with tough protection cage | | | | | | | | | | | | | | | | | | |
| Operating time (18V / 14.4V) | 4.2Ah (LS type): Approx. 24 hrs / 2.0Ah (LF type): Approx. 11 hrs | | | | | | | | | | | | | | | | | | |
| Size (LxHxW) | 344 x 280 x 239mm | | | | | | | | | | | | | | | | | | |

BATTERIES AND CHARGER

| VOLTAGE (V) / CAPACITY (AH) | MODEL / FEATURES | | |
|-----------------------------|---|---|--|
| 28.8V 3.0Ah | EY 9L82 B <ul style="list-style-type: none"> ■ Voltage 28.8V ■ Battery capacity accord. to IEC (technology) 3.0Ah (Li-ion) |  | |
| 21.6V 4.2Ah | EY 9L62 B <ul style="list-style-type: none"> ■ Voltage 21.6V ■ Battery capacity accord. to IEC (technology) 4.2Ah (Li-ion) |  | |
| 18V 5.0Ah | EY 9L54 B <ul style="list-style-type: none"> ■ Voltage 18V ■ Battery capacity accord. to IEC (technology) 5.0Ah (Li-ion) |  | |
| 18V 4.2Ah | EY 9L51 B <ul style="list-style-type: none"> ■ Voltage 18V ■ Battery capacity accord. to IEC (technology) 4.2Ah (Li-ion) |  | |
| 18V 3.0Ah | EY 9L53 B <ul style="list-style-type: none"> ■ Voltage 18V ■ Battery capacity accord. to IEC (technology) 3.0Ah (Li-ion) |  | |
| 18V 2.0Ah | EY 9L52 B <ul style="list-style-type: none"> ■ Voltage 18V ■ Battery capacity accord. to IEC (technology) 2.0Ah (Li-ion) |  | |
| 14.4V 4.2Ah | EY 9L45 B <ul style="list-style-type: none"> ■ Voltage 14.4V ■ Battery capacity accord. to IEC (technology) 4.2Ah (Li-ion) |  | |
| 14.4V 2.0Ah | EY 9L47 B <ul style="list-style-type: none"> ■ Voltage 14.4V ■ Battery capacity accord. to IEC (technology) 2.0Ah (Li-ion) |  | |

BATTERIES AND CHARGER

| VOLTAGE (V) / CAPACITY (AH) | | MODEL / FEATURES | | |
|-----------------------------|-------|--|--|--|
| 10.8V | 1.5Ah |  EY 9L32 B <ul style="list-style-type: none"> Voltage 10.8V Battery capacity accord. to IEC (technology) 1.5Ah (Li-ion) | | |
| 3.6V | 1.5Ah |  EY 9L10 B <ul style="list-style-type: none"> Voltage 3.6V Battery capacity accord. to IEC (technology) 1.5Ah (Li-ion) | | |
| 24V | 2.8Ah |  EY 9210 B <ul style="list-style-type: none"> Voltage 24V Battery capacity accord. to IEC (technology) 2.8Ah (Li-ion) | | |
| 15.6V | 2.8Ah |  EY 9230 B <ul style="list-style-type: none"> Voltage 15.6V Battery capacity accord. to IEC (technology) 2.8Ah (Ni-MH) | | |
| 12V | 2.8Ah |  EY 9200 B <ul style="list-style-type: none"> Voltage 12V Battery capacity accord. to IEC (technology) 2.8Ah (Ni-MH) | | |
| 7.2V | 2.8Ah |  EY 9268 B <ul style="list-style-type: none"> Voltage 7.2V Battery capacity accord. to IEC (technology) 2.8Ah (Ni-MH) | | |
| 2.4V | 2.8Ah |  EY 9221 B <ul style="list-style-type: none"> Voltage 2.4V Battery capacity accord. to IEC (technology) 2.8Ah (Ni-MH) | | |
| | |  EY 0L82 B <ul style="list-style-type: none"> 14.4 – 28.8V Quick charging system incl. 14.4V / 1.5Ah for all Li-ion battery types | | |
| | |  EY 0L32 B <ul style="list-style-type: none"> 10.8V Charging system for EY 9L32 B | | |
| | |  EY 0L11 B <ul style="list-style-type: none"> 2.4 – 3.6V Quick charging system for Ni-MH- and Li-ion battery types (excl. EY 9021 B) | | |
| | |  EY 0L10 B <ul style="list-style-type: none"> 2.4 – 3.6V Quick charging system for Ni-Cd-, Ni-MH- and Li-ion-battery types (excl. EY 9221 B) | | |
| | |  EY 0110 B <ul style="list-style-type: none"> 7.2 – 24V Quick charging system for all Ni-Cd- and Ni-MH battery types | | |

DRILL CHUCKS AND OTHER ACCESSORIES

| | MODEL / FEATURES | | |
|---|--|--|--|
|  | EY 9 HX 405 E <ul style="list-style-type: none"> ■ 13mm Chuck ■ For EY 7440 and Power Cosmo | | |
|  | EY 9 HX 411 E <ul style="list-style-type: none"> ■ 13mm Chuck ■ For EY 74A1, EY 7450, EY 7442, EY 7441 and EY 7940 | | |
|  | EY 9 HX 412 E <ul style="list-style-type: none"> ■ 13mm Chuck ■ For EY 7950 | | |
|  | EY 9 HX 413 E <ul style="list-style-type: none"> ■ 13mm Chuck ■ For EY 74A2 / EY 79A2 | | |
|  | EY 9 HX 111 E <ul style="list-style-type: none"> ■ Adapter ■ For EY 6535, EY 7549, EY 7541, EY 75A2, EY 7547, EY 7551 | | |
|  | EY 9 X 004 E <ul style="list-style-type: none"> ■ Dust collection cup ■ For EY 6813 and EY 7880 | | |
|  | EY 9 X 005 E <ul style="list-style-type: none"> ■ Dust collection cup ■ For EY 7840 and EY 78A1 | | |
|  | EY 9 X 008 E <ul style="list-style-type: none"> ■ Adapter for foil packs ■ For EY 3654 | | |
|  | EY 9 X 009 E <ul style="list-style-type: none"> ■ Hose adapter for saws ■ For EY 4541 | | |
|  | EY 9 X 011 E <ul style="list-style-type: none"> ■ Rip fence ■ For EY 4541 | | |
|  | EY 9 X 012 E <ul style="list-style-type: none"> ■ Hose adapter ■ For EY 4542 and EY45A2 | | |
|  | EY 9 X 013 E <ul style="list-style-type: none"> ■ Plunger ■ For EY 3640 / EY 3641 / EY 3610 | | |
|  | EY 9 X 016 E <ul style="list-style-type: none"> ■ Dust adapter jigsaw ■ For EY 4550 | | |
|  | EY 9 X 017 E <ul style="list-style-type: none"> ■ Cartridge plunger ■ Adapter for 3.6V sealing gun | | |

PRODUCT OVERVIEW

| | | | | | | |
|--|------------------------------------|--|--|--|--|---|
| 28.8V | | 21.6V | | 18V | | |
| | | | | | | |
| EY 7880 LP2C / X SDS-plus Rotary Hammer | EY 7460 LS2S Drill & Driver | EY 7960 LS2S Hammer Drill & Driver | EY 7450 LJ2S / X Drill & Driver | EY 7950 LJ2S / X Hammer Drill & Driver | EY 7552 LJ2S / X Impact Wrench | EY 4550 X Jigsaw |
| 18V / 14.4V | | 18V | | | | |
| | | | | | | |
| EY 74A2 LJ2G / PN2G / X Drill & Driver | EY 74A1 X Drill & Driver | EY 75A7 LJ2G / PN2G / X Impact Driver | EY 75A2 LJ2G / PN2G / X Impact Driver | EY 79A2 LJ2G / PN2G / X Hammer Drill & Driver | EY 78A1 LJ2G / PN2G / X SDS-plus type Rotary Hammer | EY 45A1 LJ2G / X Reciprocating Saw |
| 18V / 14.4V | | | | 14.4V | | |
| | | | | | | |
| EY 45A2 LJ2G / XM / XW Multi Purpose Cutter | EY 46A2 LJ2G / X Angle Grinder | EY 37A1 B Blower | EY 37A2 B Radio | EY 7443 LS2S / X Auto Drill & Driver | EY 7441 LS2S / X Drill & Driver | EY 7549 LS2S / X Multi Impact Driver |
| 14.4V | | | | | 21.6V / 18V / 14.4V | |
| | | | | | | |
| EY 7940 LS2S / X Hammer Drill & Driver | EY 4541 LS1S / X Jigsaw | EY 3640 LS1S / K Sealing Gun | EY 3641 LS1S / K Sealing Gun | EY 3743 B Vacuum Cleaner | EY 37C1 B Flashlight | EY 37C2 B Flashlight |
| 10.8V | | 3.6V | | | | |
| | | | | | | |
| EY 3732 B Flashlight | EY 7410 LA2S / LA1C Screwdriver | EY 7411 LA1S / LA1C Screwdriver | EY 3610 LA1J Sealing Gun | | | |

MODEL NUMBER

| | | |
|---|---|---|
| Example EY 74 A2 LJ 2G | Product type EY 0000 XX XX | Voltage EY 0000 XX XX |
| <ul style="list-style-type: none"> Incl. second 18V battery pack 4.2Ah battery 14.4 / 18V DUAL Drill & Driver with Li-ion battery type | <ul style="list-style-type: none"> EY 79 Hammer Drill & Driver EY 78 SDS-plus type Rotary Hammer EY 75 Impact Wrench & Driver EY 74 / EY 64 Drill & Driver EY 74 / EY 62 Screwdriver EY 46 Angle Grinder EY 45 Saws EY 37 Flashlight EY 36 / EY 36 Sealing Gun Ni-MH battery type Li-ion battery type | <ul style="list-style-type: none"> A1 / A2 / A7 14.4 / 18V DUAL C1 / C2 14.4 / 18 / 21.6V 80 28.8V 60 21.6V 50 / 52 18V 32 15.6V (Ni-MH) 40 / 41 / 43 / 49 14.4V 09 12V 30 / 32 10.8V (Li-ion) 54 7.2V 10 / 11 3.6V 20 2.4V |
| Battery type EY 0000 XX XX | Delivery EY 0000 XX XX | |
| <ul style="list-style-type: none"> LJ 5.0Ah battery LS 4.2Ah battery PN 3.0Ah battery LP 3.0Ah battery N 2.8Ah battery LF 2.0Ah battery LA 1.5Ah battery B Without battery and charger X Without battery and charger | <ul style="list-style-type: none"> 2S / 2C Incl. second battery pack 2G Incl. second 18V battery pack 2F Incl. second 14.4V battery pack 2L Incl. second 10.8V / 1.5 Ah battery pack and one flashlight 1J / 1S / 1C Incl. one battery pack 1G Incl. one 18V battery pack Q Incl. charger W Incl. second battery pack (Ni-MH) K Incl. plastic box, without battery and charger M Incl. carbide-tipped blade for metal W Incl. second battery pack (Li-ion) | |

Panasonic®

Panasonic Power Tools

'Panasonic House' Willoughby Road
Bracknell, Berkshire
RG12 8FP United Kingdom

Panasonic Electric Works Europe AG

The design and specification of products are constantly changing in the interest of improvement. Whilst every care has been taken in preparation of this catalogue, some changes may not have been indicated and may have occurred after publication. Please check with your Panasonic dealer for details. Panasonic Electric Works Europe AG cannot accept responsibility for any errors and omissions.

Produced in Germany 07/2016

© 2016 Panasonic Electric Works Europe AG

DEALER'S STAMP

www.panasonic-powertools.eu